

Revised⁵ Report on the Algorithmic Language Scheme

H. ABELSON, R.K. DYBVIK, C.T. HAYNES, G.J. ROZAS, N.I. ADAMS IV, D.P. FRIEDMAN, E. KOHLBECKER, G.L. STEELE, JR., D.H. BARTLEY, R. HALSTEAD, D. OXLEY, G.J. SUSSMAN, G. BROOKS, C. HANSON, K.M. PITMAN AND M. WAND

Editors: Richard Kelsey, William Clinger, and Jonathan Rees

Dedicated to the Memory of Robert Hieb

Abstract. The report gives a defining description of the programming language Scheme. Scheme is a statically scoped and properly tail-recursive dialect of the Lisp programming language invented by Guy Lewis Steele, Jr. and Gerald Jay Sussman. It was designed to have an exceptionally clear and simple semantics and few different ways to form expressions. A wide variety of programming paradigms, including imperative, functional, and message passing styles, find convenient expression in Scheme.

The introduction offers a brief history of the language and of the report.

The first three chapters present the fundamental ideas of the language and describe the notational conventions used for describing the language and for writing programs in the language.

Sections 5 and 6 describe the syntax and semantics of expressions, programs, and definitions.

Section 7 describes Scheme's built-in procedures, which include all of the language's data manipulation and input/output primitives.

Section 8 provides a formal syntax for Scheme written in extended BNF, along with a formal denotational semantics. An example of the use of the language follows the formal syntax and semantics.

The report concludes with a list of references and an alphabetic index and is followed by a short list of clarifications and corrections.

Keywords: Scheme, Lisp, programming languages

1. Introduction

Programming languages should be designed not by piling feature on top of feature, but by removing the weaknesses and restrictions that make additional features appear necessary. Scheme demonstrates that a very small number of rules for forming expressions, with no restrictions on how they are composed, suffice to form a practical and efficient programming language that is flexible enough to support most of the major programming paradigms in use today.

Scheme was one of the first programming languages to incorporate first class procedures as in the lambda calculus, thereby proving the usefulness of static scope rules and block structure in a dynamically typed language. Scheme was the first major dialect of Lisp to distinguish procedures from lambda expressions and symbols, to use a single lexical environment for all variables, and to evaluate the operator position of a procedure call in the same way as an operand position. By relying entirely on procedure calls to express iteration,

Scheme emphasized the fact that tail-recursive procedure calls are essentially goto's that pass arguments. Scheme was the first widely used programming language to embrace first class escape procedures, from which all previously known sequential control structures can be synthesized. A subsequent version of Scheme introduced the concept of exact and inexact numbers, an extension of Common Lisp's generic arithmetic. More recently, Scheme became the first programming language to support hygienic macros, which permit the syntax of a block-structured language to be extended in a consistent and reliable manner.

Background. The first description of Scheme was written in 1975 [28]. A revised report [25] appeared in 1978, which described the evolution of the language as its MIT implementation was upgraded to support an innovative compiler [26]. Three distinct projects began in 1981 and 1982 to use variants of Scheme for courses at MIT, Yale, and Indiana University [10, 17, 21]. An introductory computer science textbook using Scheme was published in 1984 [1].

As Scheme became more widespread, local dialects began to diverge until students and researchers occasionally found it difficult to understand code written at other sites. Fifteen representatives of the major implementations of Scheme therefore met in October 1984 to work toward a better and more widely accepted standard for Scheme. Their report [4] was published at MIT and Indiana University in the summer of 1985. Further revision took place in the spring of 1986 [23], and in the spring of 1988 [6]. The present report reflects further revisions agreed upon in a meeting at Xerox PARC in June 1992.

We intend this report to belong to the entire Scheme community, and so we grant permission to copy it in whole or in part without fee. In particular, we encourage implementors of Scheme to use this report as a starting point for manuals and other documentation, modifying it as necessary.

2. Overview of Scheme

2.1. Semantics

This section gives an overview of Scheme's semantics. A detailed informal semantics is the subject of Sections 4 through 7. For reference purposes, Section 8.2 provides a formal semantics of Scheme.

Following Algol, Scheme is a statically scoped programming language. Each use of a variable is associated with a lexically apparent binding of that variable.

Scheme has latent as opposed to manifest types. Types are associated with values (also called objects) rather than with variables. (Some authors refer to languages with latent types as weakly typed or dynamically typed languages.) Other languages with latent types are APL, Snobol, and other dialects of Lisp. Languages with manifest types (sometimes referred to as strongly typed or statically typed languages) include Algol 60, Pascal, and C.

All objects created in the course of a Scheme computation, including procedures and continuations, have unlimited extent. No Scheme object is ever destroyed. The reason that implementations of Scheme do not (usually!) run out of storage is that they are permitted to reclaim the storage occupied by an object if they can prove that the object cannot possibly

matter to any future computation. Other languages in which most objects have unlimited extent include APL and other Lisp dialects.

Implementations of Scheme are required to be properly tail-recursive. This allows the execution of an iterative computation in constant space, even if the iterative computation is described by a syntactically recursive procedure. Thus with a properly tail-recursive implementation, iteration can be expressed using the ordinary procedure-call mechanics, so that special iteration constructs are useful only as syntactic sugar. See Section 4.5.

Scheme procedures are objects in their own right. Procedures can be created dynamically, stored in data structures, returned as results of procedures, and so on. Other languages with these properties include Common Lisp and ML.

One distinguishing feature of Scheme is that continuations, which in most other languages only operate behind the scenes, also have “first-class” status. Continuations are useful for implementing a wide variety of advanced control constructs, including nonlocal exits, backtracking, and coroutines. See Section 7.4.

Arguments to Scheme procedures are always passed by value, which means that the actual argument expressions are evaluated before the procedure gains control, whether the procedure needs the result of the evaluation or not. ML, C, and APL are three other languages that always pass arguments by value. This is distinct from the lazy-evaluation semantics of Haskell, or the call-by-name semantics of Algol 60, where an argument expression is not evaluated unless its value is needed by the procedure.

Scheme’s model of arithmetic is designed to remain as independent as possible of the particular ways in which numbers are represented within a computer. In Scheme, every integer is a rational number, every rational is a real, and every real is a complex number. Thus the distinction between integer and real arithmetic, so important to many programming languages, does not appear in Scheme. In its place is a distinction between exact arithmetic, which corresponds to the mathematical ideal, and inexact arithmetic on approximations. As in Common Lisp, exact arithmetic is not limited to integers.

2.2. *Syntax*

Scheme, like most dialects of Lisp, employs a fully parenthesized prefix notation for programs and (other) data; the grammar of Scheme generates a sublanguage of the language used for data. An important consequence of this simple, uniform representation is the susceptibility of Scheme programs and data to uniform treatment by other Scheme programs. For example, the `eval` procedure evaluates a Scheme program expressed as data.

The `read` procedure performs syntactic as well as lexical decomposition of the data it reads. The `read` procedure parses its input as data (Section 8.1.2), not as program.

The formal syntax of Scheme is described in Section 8.1.

2.3. *Notation and terminology*

2.3.1. *Primitive, library, and optional features.* It is required that every implementation of Scheme support all features that are not marked as being *optional*. Implementations are free to omit optional features of Scheme or to add extensions, provided the extensions are

not in conflict with the language reported here. In particular, implementations must support portable code by providing a syntactic mode that preempts no lexical conventions of this report.

To aid in understanding and implementing Scheme, some features are marked as *library*. These can be easily implemented in terms of the other, primitive, features. They are redundant in the strict sense of the word, but they capture common patterns of usage, and are therefore provided as convenient abbreviations.

2.3.2. Error situations and unspecified behavior. When speaking of an error situation, this report uses the phrase “an error is signalled” to indicate that implementations must detect and report the error. If such wording does not appear in the discussion of an error, then implementations are not required to detect or report the error, though they are encouraged to do so. An error situation that implementations are not required to detect is usually referred to simply as “an error.”

For example, it is an error for a procedure to be passed an argument that the procedure is not explicitly specified to handle, even though such domain errors are seldom mentioned in this report. Implementations may extend a procedure’s domain of definition to include such arguments.

This report uses the phrase “may report a violation of an implementation restriction” to indicate circumstances under which an implementation is permitted to report that it is unable to continue execution of a correct program because of some restriction imposed by the implementation. Implementation restrictions are of course discouraged, but implementations are encouraged to report violations of implementation restrictions.

For example, an implementation may report a violation of an implementation restriction if it does not have enough storage to run a program.

If the value of an expression is said to be “unspecified,” then the expression must evaluate to some object without signalling an error, but the value depends on the implementation; this report explicitly does not say what value should be returned.

2.3.3. Entry format. Sections 5 and 7 are organized into entries. Each entry describes one language feature or a group of related features, where a feature is either a syntactic construct or a built-in procedure. An entry begins with one or more header lines of the form

template *category*

for required, primitive features, or

template *qualifier category*

where *qualifier* is either “library” or “optional” as defined in Section 2.3.1.

If *category* is “syntax”, the entry describes an expression type, and the template gives the syntax of the expression type. Components of expressions are designated by syntactic variables, which are written using angle brackets, for example, (expression), (variable). Syntactic variables should be understood to denote segments of program text; for example,

$\langle \text{expression} \rangle$ stands for any string of characters which is a syntactically valid expression. The notation

$\langle \text{thing}_1 \rangle \dots$

indicates zero or more occurrences of a $\langle \text{thing} \rangle$, and

$\langle \text{thing}_1 \rangle \langle \text{thing}_2 \rangle \dots$

indicates one or more occurrences of a $\langle \text{thing} \rangle$.

If *category* is “procedure”, then the entry describes a procedure, and the header line gives a template for a call to the procedure. Argument names in the template are *italicized*. Thus the header line

`(vector-ref vector k)` procedure

indicates that the built-in procedure `vector-ref` takes two arguments, a vector *vector* and an exact non-negative integer *k* (see below). The header lines

`(make-vector k)` procedure
`(make-vector k fill)` procedure

indicate that the `make-vector` procedure must be defined to take either one or two arguments.

It is an error for an operation to be presented with an argument that it is not specified to handle. For succinctness, we follow the convention that if an argument name is also the name of a type listed in Section 4.2, then that argument must be of the named type. For example, the header line for `vector-ref` given above dictates that the first argument to `vector-ref` must be a vector. The following naming conventions also imply type restrictions:

<i>obj</i>	any object
<i>list, list</i> ₁ , ..., <i>list</i> _{<i>j</i>} , ...	list (see Section 7.3.2)
<i>z, z</i> ₁ , ..., <i>z</i> _{<i>j</i>} , ...	complex number
<i>x, x</i> ₁ , ..., <i>x</i> _{<i>j</i>} , ...	real number
<i>y, y</i> ₁ , ..., <i>y</i> _{<i>j</i>} , ...	real number
<i>q, q</i> ₁ , ..., <i>q</i> _{<i>j</i>} , ...	rational number
<i>n, n</i> ₁ , ..., <i>n</i> _{<i>j</i>} , ...	integer
<i>k, k</i> ₁ , ..., <i>k</i> _{<i>j</i>} , ...	exact nonnegative integer

2.3.4. Evaluation examples. The symbol “ \Longrightarrow ” used in program examples should be read “evaluates to.” For example,

means that the expression `(* 5 8)` evaluates to the object 40. Or, more precisely: the expression given by the sequence of characters “`(* 5 8)`” evaluates, in the initial environment, to an object that may be represented externally by the sequence of characters “40”. See Section 4.3 for a discussion of external representations of objects.

2.3.5. Naming conventions. By convention, the names of procedures that always return a boolean value usually end in “?”. Such procedures are called predicates.

By convention, the names of procedures that store values into previously allocated locations (see Section 4.4) usually end in “!”. Such procedures are called mutation procedures. By convention, the value returned by a mutation procedure is unspecified.

By convention, “->” appears within the names of procedures that take an object of one type and return an analogous object of another type. For example, `list->vector` takes a list and returns a vector whose elements are the same as those of the list.

3. Lexical conventions

This section gives an informal account of some of the lexical conventions used in writing Scheme programs. For a formal syntax of Scheme, see Section 8.1.

Upper and lower case forms of a letter are never distinguished except within character and string constants. For example, `Foo` is the same identifier as `F00`, and `#x1AB` is the same number as `#X1ab`.

3.1. Identifiers

Most identifiers allowed by other programming languages are also acceptable to Scheme. The precise rules for forming identifiers vary among implementations of Scheme, but in all implementations a sequence of letters, digits, and “extended alphabetic characters” that begins with a character that cannot begin a number is an identifier. In addition, `+`, `-`, and `...` are identifiers. Here are some examples of identifiers:

<code>lambda</code>	<code>q</code>
<code>list->vector</code>	<code>soup</code>
<code>+</code>	<code>V17a</code>
<code><=?</code>	<code>a34kTMNs</code>
<code>the-word-recursion-has-many-meanings</code>	

Extended alphabetic characters may be used within identifiers as if they were letters. The following are extended alphabetic characters:

`! $ % & * + - . / : < = > ? @ ^ _ ~`

See Section 8.11 for a formal syntax of identifiers.

Identifiers have two uses within Scheme programs:

- Any identifier may be used as a variable or as a syntactic keyword (see Sections 4.1 and 5.3).

- When an identifier appears as a literal or within a literal (see Section 5.1.2), it is being used to denote a *symbol* (see Section 7.3.3).

3.2. *Whitespace and comments*

Whitespace characters are spaces and newlines. (Implementations typically provide additional whitespace characters such as tab or page break.) Whitespace is used for improved readability and as necessary to separate tokens from each other, a token being an indivisible lexical unit such as an identifier or number, but is otherwise insignificant. Whitespace may occur between any two tokens, but not within a token. Whitespace may also occur inside a string, where it is significant.

A semicolon (;) indicates the start of a comment. The comment continues to the end of the line on which the semicolon appears. Comments are invisible to Scheme, but the end of the line is visible as whitespace. This prevents a comment from appearing in the middle of an identifier or number.

```
;;; The FACT procedure computes the factorial
;;; of a nonnegative integer.
(define fact
  (lambda (n)
    (if (= n 0)
        1 ;Base case: return 1
        (* n (fact (-n 1))))))
```

3.3. *Other notations*

For a description of the notations used for numbers, see Section 7.2.

- . + - These are used in numbers, and may also occur anywhere in an identifier except as the first character. A delimited plus or minus sign by itself is also an identifier. A delimited period (not occurring within a number or identifier) is used in the notation for pairs (Section 7.3.2), and to indicate a rest-parameter in a formal parameter list (Section 5.1.4). A delimited sequence of three successive periods is also an identifier.
- () Parentheses are used for grouping and to notate lists (Section 7.3.2).
- ' The single quote character is used to indicate literal data (Section 5.1.2).
- ` The backquote character is used to indicate almost-constant data (Section 5.2.6).
- , ,@ The character comma and the sequence comma at-sign are used in conjunction with backquote (Section 5.2.6).
- " The double quote character is used to delimit strings (Section 7.3.5).
- \ Backslash is used in the syntax for character constants (Section 7.3.4) and as an escape character within string constants (Section 7.3.5).
- [] { } | Left and right square brackets and curly braces and vertical bar are reserved for possible future extensions to the language.

Sharp sign is used for a variety of purposes depending on the character that immediately follows it:

#t #f These are the boolean constants (Section 7.3.1).
 #\ This introduces a character constant (Section 7.3.4).
 #(This introduces a vector constant (Section 7.3.6). Vector constants are terminated by).
 #e #i #b #o #d #x These are used in the notation for numbers (Section 7.2.4).

4. Basic concepts

4.1. Variables, syntactic keywords, and regions

An identifier may name a type of syntax, or it may name a location where a value can be stored. An identifier that names a type of syntax is called a *syntactic keyword* and is said to be *bound* to that syntax. An identifier that names a location is called a *variable* and is said to be *bound* to that location. The set of all visible bindings in effect at some point in a program is known as the *environment* in effect at that point. The value stored in the location to which a variable is bound is called the variable's value. By abuse of terminology, the variable is sometimes said to name the value or to be bound to the value. This is not quite accurate, but confusion rarely results from this practice.

Certain expression types are used to create new kinds of syntax and bind syntactic keywords to those new syntaxes, while other expression types create new locations and bind variables to those locations. These expression types are called *binding constructs*. Those that bind syntactic keywords are listed in Section 5.3. The most fundamental of the variable binding constructs is the `lambda` expression, because all other variable binding constructs can be explained in terms of `lambda` expressions. The other variable binding constructs are `let`, `let*`, `letrec`, and `do` expressions (see Sections 5.1.4, 5.2.2, and 5.2.4).

Like Algol and Pascal, and unlike most other dialects of Lisp except for Common Lisp, Scheme is a statically scoped language with block structure. To each place where an identifier is bound in a program there corresponds a *region* of the program text within which the binding is visible. The region is determined by the particular binding construct that establishes the binding; if the binding is established by a `lambda` expression, for example, then its region is the entire `lambda` expression. Every mention of an identifier refers to the binding of the identifier that established the innermost of the regions containing the use. If there is no binding of the identifier whose region contains the use, then the use refers to the binding for the variable in the top level environment, if any (Sections 5 and 7); if there is no binding for the identifier, it is said to be *unbound*.

4.2. Disjointness of types

No object satisfies more than one of the following predicates:

<code>boolean?</code>	<code>pair?</code>
<code>symbol?</code>	<code>number?</code>

```

char?           string?
vector?        port?
procedure?

```

These predicates define the types *boolean*, *pair*, *symbol*, *number*, *char* (or *character*), *string*, *vector*, *port*, and *procedure*. The empty list is a special object of its own type; it satisfies none of the above predicates.

Although there is a separate boolean type, any Scheme value can be used as a boolean value for the purpose of a conditional test. As explained in Section 7.3.1, all values count as true in such a test except for #f. This report uses the word “true” to refer to any Scheme value except #f, and the word “false” to refer to #f.

4.3. External representations

An important concept in Scheme (and Lisp) is that of the *external representation* of an object as a sequence of characters. For example, an external representation of the integer 28 is the sequence of characters “28”, and an external representation of a list consisting of the integers 8 and 13 is the sequence of characters “(8 13)”.

The external representation of an object is not necessarily unique. The integer 28 also has representations “#e28.000” and “#x1c”, and the list in the previous paragraph also has the representations “(08 13)” and “(8 . (13. ()))” (see Section 7.3.2).

Many objects have standard external representations, but some, such as procedures, do not have standard representations (although particular implementations may define representations for them).

An external representation may be written in a program to obtain the corresponding object (see quote, Section 5.1.2).

External representations can also be used for input and output. The procedure *read* (Section 7.6.2) parses external representations, and the procedure *write* (Section 7.6.3) generates them. Together, they provide an elegant and powerful input/output facility.

Note that the sequence of characters “(+ 2 6)” is *not* an external representation of the integer 8, even though it *is* an expression evaluating to the integer 8; rather, it is an external representation of a three-element list, the elements of which are the symbol + and the integers 2 and 6. Scheme’s syntax has the property that any sequence of characters that is an expression is also the external representation of some object. This can lead to confusion, since it may not be obvious out of context whether a given sequence of characters is intended to denote data or program, but it is also a source of power, since it facilitates writing programs such as interpreters and compilers that treat programs as data (or vice versa).

The syntax of external representations of various kinds of objects accompanies the description of the primitives for manipulating the objects in the appropriate subsections of Section 7.

4.4. Storage model

Variables and objects such as pairs, vectors, and strings implicitly denote locations or sequences of locations. A string, for example, denotes as many locations as there are

characters in the string. (These locations need not correspond to a full machine word.) A new value may be stored into one of these locations using the `string-set!` procedure, but the string continues to denote the same locations as before.

An object fetched from a location, by a variable reference or by a procedure such as `car`, `vector-ref`, or `string-ref`, is equivalent in the sense of `eqv?` (Section 7.1) to the object last stored in the location before the fetch.

Every location is marked to show whether it is in use. No variable or object ever refers to a location that is not in use. Whenever this report speaks of storage being allocated for a variable or object, what is meant is that an appropriate number of locations are chosen from the set of locations that are not in use, and the chosen locations are marked to indicate that they are now in use before the variable or object is made to denote them.

In many systems it is desirable for constants (i.e., the values of literal expressions) to reside in read-only-memory. To express this, it is convenient to imagine that every object that denotes locations is associated with a flag telling whether that object is mutable or immutable. In such systems literal constants and the strings returned by `symbol->string` are immutable objects, while all objects created by the other procedures listed in this report are mutable. It is an error to attempt to store a new value into a location that is denoted by an immutable object.

4.5. *Proper tail recursion*

Implementations of Scheme are required to be *properly tail-recursive*. Procedure calls that occur in certain syntactic contexts defined below are ‘tail calls’. A Scheme implementation is properly tail-recursive if it supports an unbounded number of active tail calls. A call is *active* if the called procedure may still return. Note that this includes calls that may be returned from either by the current continuation or by continuations captured earlier by `call-with-current-continuation` that are later invoked. In the absence of captured continuations, calls could return at most once and the active calls would be those that had not yet returned. A formal definition of proper tail recursion can be found in [8].

Rationale: Intuitively, no space is needed for an active tail call because the continuation that is used in the tail call has the same semantics as the continuation passed to the procedure containing the call. Although an improper implementation might use a new continuation in the call, a return to this new continuation would be followed immediately by a return to the continuation passed to the procedure. A properly tail-recursive implementation returns to that continuation directly.

Proper tail recursion was one of the central ideas in Steele and Sussman’s original version of Scheme. Their first Scheme interpreter implemented both functions and actors. Control flow was expressed using actors, which differed from functions in that they passed their results on to another actor instead of returning to a caller. In the terminology of this section, each actor finished with a tail call to another actor.

Steele and Sussman later observed that in their interpreter the code for dealing with actors was identical to that for functions and thus there was no need to include both in the language.

A *tail call* is a procedure call that occurs in a *tail context*. Tail contexts are defined inductively. Note that a tail context is always determined with respect to a particular lambda expression.

- The last expression within the body of a lambda expression, shown as $\langle \text{tail expression} \rangle$ below, occurs in a tail context.

```
( lambda (formals)
  (definition)* (expression)*  $\langle \text{tail expression} \rangle$ )
```

- If one of the following expressions is in a tail context, then the subexpressions shown as $\langle \text{tail expression} \rangle$ are in a tail context. These were derived from rules in the grammar given in Section 8 by replacing some occurrences of $\langle \text{expression} \rangle$ with $\langle \text{tail expression} \rangle$. Only those rules that contain tail contexts are shown here.

```
(if (expression)  $\langle \text{tail expression} \rangle$  (tail expression))
(if (expression) (tail expression))
```

```
(cond (cond clause)+
      (cond (cond clause)* (else (tail sequence))))
```

```
(case (expression)
      (case clause)+
      (case (expression)
        (case clause)*
        ( else (tail sequence))))
```

```
(and (expression)*  $\langle \text{tail expression} \rangle$ )
(or (expression)*  $\langle \text{tail expression} \rangle$ )
```

```
(let ((binding spec)* (tail body))
      (let (variable) ((binding spec)* (tail body))
        (let* ((binding spec)* (tail body))
          (letrec ((binding spec)* (tail body))
```

```
(let-syntax ((syntax spec)* (tail body))
      (letrec-syntax ((syntax spec)* (tail body))
```

```
(begin (tail sequence))
```

```
(do ((iteration spec)*
      ((test) (tail sequence))
      (expression)*
```

where

```
(cond clause)  $\longrightarrow$  ( (test) (tail sequence))
(case clause)  $\longrightarrow$  ((datum)* (tail sequence))
```

$\langle \text{tail body} \rangle \longrightarrow \langle \text{definition} \rangle^* \langle \text{tail sequence} \rangle$
 $\langle \text{tail sequence} \rangle \longrightarrow \langle \text{expression} \rangle^* \langle \text{tail expression} \rangle$

- If a `cond` expression is in a tail context, and has a clause of the form $(\langle \text{expression}_1 \rangle \Rightarrow \langle \text{expression}_2 \rangle)$ then the (implied) call to the procedure that results from the evaluation of $\langle \text{expression}_2 \rangle$ is in a tail context. $\langle \text{expression}_2 \rangle$ itself is not in a tail context.

Certain built-in procedures are also required to perform tail calls. The first argument passed to `apply` and to `call-with-current-continuation`, and the second argument passed to `call-with-values`, must be called via a tail call. Similarly, `eval` must evaluate its argument as if it were in tail position within the `eval` procedure.

In the following example the only tail call is the call to `f`. None of the calls to `g` or `h` are tail calls. The reference to `x` is in a tail context, but it is not a call and thus is not a tail call.

```

(lambda ()
  (if (g)
      (let ((x (h)))
        x)
      (and (g) (f))))

```

Note: Implementations are allowed, but not required, to recognize that some nontail calls, such as the call to `h` above, can be evaluated as though they were tail calls. In the example above, the `let` expression could be compiled as a tail call to `h`. (The possibility of `h` returning an unexpected number of values can be ignored, because in that case the effect of the `let` is explicitly unspecified and implementation-dependent.)

5. Expressions

Expression types are categorized as *primitive* or *derived*. Primitive expression types include variables and procedure calls. Derived expression types are not semantically primitive, but can instead be defined as macros. With the exception of `quasiquote`, whose macro definition is complex, the derived expressions are classified as library features. Suitable definitions are given in Section 8.3.

5.1. Primitive expression types

5.1.1. Variable references.

$\langle \text{variable} \rangle$ syntax

An expression consisting of a variable (Section 4.1) is a variable reference. The value of the variable reference is the value stored in the location to which the variable is bound. It is an error to reference an unbound variable.

```
(define x 28)
x                               ⇒ 28
```

5.1.2. *Literal expressions.*

```
(quote (datum))                syntax
'(datum)                       syntax
(constant)                     syntax
```

(quote <datum>) evaluates to <datum>. <Datum> may be any external representation of a Scheme object (see Section 4.3). This notation is used to include literal constants in Scheme code.

```
(quote a)                       ⇒ a
(quote #(a b c))                ⇒ #(a b c)
(quote (+ 1 2))                ⇒ (+ 1 2)
```

(quote <datum>) may be abbreviated as '<datum>'. The two notations are equivalent in all respects.

```
'a                               ⇒ a
'#(a b c)                       ⇒ #(a b c)
'()                              ⇒ ()
'(+ 1 2)                        ⇒ (+ 1 2)
'(quote a)                      ⇒ (quote a)
''a                              ⇒ (quote a)
```

Numerical constants, string constants, character constants, and boolean constants evaluate “to themselves”; they need not be quoted.

```
"abc"                           ⇒ "abc"
"abc"                           ⇒ "abc"
'145932                         ⇒ 145932
145932                         ⇒ 145932
'#t                             ⇒ #t
#t                              ⇒ #t
```

As noted in Section 4.4, it is an error to alter a constant (i.e., the value of a literal expression) using a mutation procedure like `set-car!` or `string-set!`.

5.1.3. *Procedure calls.*

```
((operator) (operand1) ...)
```

syntax

A procedure call is written by simply enclosing in parentheses expressions for the procedure to be called and the arguments to be passed to it. The operator and operand expressions are evaluated (in an unspecified order) and the resulting procedure is passed the resulting arguments.

(+ 3 4)	⇒	7
((if #f + *) 3 4)	⇒	12

A number of procedures are available as the values of variables in the initial environment; for example, the addition and multiplication procedures in the above examples are the values of the variables `+` and `*`. New procedures are created by evaluating `lambda` expressions (see Section 5.1.4).

Procedure calls may return any number of values (see `values` in Section 7.4). With the exception of `values` the procedures available in the initial environment return one value or, for procedures such as `apply`, pass on the values returned by a call to one of their arguments.

Procedure calls are also called *combinations*.

Note: In contrast to other dialects of Lisp, the order of evaluation is unspecified, and the operator expression and the operand expressions are always evaluated with the same evaluation rules.

Note: Although the order of evaluation is otherwise unspecified, the effect of any concurrent evaluation of the operator and operand expressions is constrained to be consistent with some sequential order of evaluation. The order of evaluation may be chosen differently for each procedure call.

Note: In many dialects of Lisp, the empty combination, `()`, is a legitimate expression. In Scheme, combinations must have at least one subexpression, so `()` is not a syntactically valid expression.

5.1.4. Procedures.

`(lambda (formals) (body))` syntax

Syntax: `⟨Formals⟩` should be a formal arguments list as described below, and `⟨body⟩` should be a sequence of one or more expressions.

Semantics: A `lambda` expression evaluates to a procedure. The environment in effect when the `lambda` expression was evaluated is remembered as part of the procedure. When the procedure is later called with some actual arguments, the environment in which the `lambda` expression was evaluated will be extended by binding the variables in the formal argument list to fresh locations, the corresponding actual argument values will be stored in those locations, and the expressions in the body of the `lambda` expression will be evaluated

sequentially in the extended environment. The result(s) of the last expression in the body will be returned as the result(s) of the procedure call.

```
(lambda (x) (+ x x))           ⇒ a procedure
((lambda (x) (+ x x)) 4)      ⇒ 8
```

```
(define reverse-subtract
  (lambda (x y) (- y x)))
(reverse-subtract 7 10)       ⇒ 3
```

```
(define add4
  (let ((x 4))
    (lambda (y) (+ x y))))
(add4 6)                       ⇒ 10
```

(Formals) should have one of the following forms:

- $\langle\langle\text{variable}_1\rangle \dots\rangle$: The procedure takes a fixed number of arguments; when the procedure is called, the arguments will be stored in the bindings of the corresponding variables.
- $\langle\text{variable}\rangle$: The procedure takes any number of arguments; when the procedure is called, the sequence of actual arguments is converted into a newly allocated list, and the list is stored in the binding of the $\langle\text{variable}\rangle$.
- $\langle\langle\text{variable}_1\rangle \dots \langle\text{variable}_n\rangle . \langle\text{variable}_{n+1}\rangle\rangle$: If a space-delimited period precedes the last variable, then the procedure takes n or more arguments, where n is the number of formal arguments before the period (there must be at least one). The value stored in the binding of the last variable will be a newly allocated list of the actual arguments left over after all the other actual arguments have been matched up against the other formal arguments.

It is an error for a $\langle\text{variable}\rangle$ to appear more than once in $\langle\text{formals}\rangle$.

```
((lambda x x) 3 4 5 6)        ⇒ (3 4 5 6)
((lambda (x y . z) z)
 3 4 5 6)                     ⇒ (5 6)
```

Each procedure created as the result of evaluating a `lambda` expression is (conceptually) tagged with a storage location, in order to make `eqv?` and `eq?` work on procedures (see Section 7.1).

5.1.5. Conditionals.

```
(if (test) (consequent) (alternate))           syntax
(if (test) (consequent))                       syntax
```

Syntax: $\langle\text{Test}\rangle$, $\langle\text{consequent}\rangle$, and $\langle\text{alternate}\rangle$ may be arbitrary expressions.

Semantics: An `if` expression is evaluated as follows: first, $\langle \text{test} \rangle$ is evaluated. If it yields a true value (see Section 7.3.1), then $\langle \text{consequent} \rangle$ is evaluated and its value(s) is(are) returned. Otherwise $\langle \text{alternate} \rangle$ is evaluated and its value(s) is(are) returned. If $\langle \text{test} \rangle$ yields a false value and no $\langle \text{alternate} \rangle$ is specified, then the result of the expression is unspecified.

```
(if (> 3 2) 'yes 'no)            $\implies$  yes
(if (> 2 3) 'yes 'no)            $\implies$  no
(if (> 3 2)
    (- 3 2)
    (+ 3 2))                     $\implies$  1
```

5.1.6. Assignments.

```
(set! <variable> <expression>) syntax
```

$\langle \text{Expression} \rangle$ is evaluated, and the resulting value is stored in the location to which $\langle \text{variable} \rangle$ is bound. $\langle \text{Variable} \rangle$ must be bound either in some region enclosing the `set!` expression or at top level. The result of the `set!` expression is unspecified.

```
(define x 2)
(+ x 1)            $\implies$  3
(set! x 4)         $\implies$  unspecified
(+ x 1)           $\implies$  5
```

5.2. Derived expression types

The constructs in this section are hygienic, as discussed in Section 5.3. For reference purposes, Section 8.3 gives macro definitions that will convert most of the constructs described in this section into the primitive constructs described in the previous section.

5.2.1. Conditionals.

```
(cond <clause1> <clause2> ...) library syntax
```

Syntax: Each $\langle \text{clause} \rangle$ should be of the form

```
((test) <expression1> ...)
```

where $\langle \text{test} \rangle$ is any expression. Alternatively, a $\langle \text{clause} \rangle$ may be of the form

```
((test) => <expression>)
```

The last $\langle \text{clause} \rangle$ may be an “else clause,” which has the form

```
(else <expression1> <expression2> ...).
```

Semantics: A `cond` expression is evaluated by evaluating the \langle test \rangle expressions of successive \langle clause \rangle s in order until one of them evaluates to a true value (see Section 7.3.1). When a \langle test \rangle evaluates to a true value, then the remaining \langle expression \rangle s in its \langle clause \rangle are evaluated in order, and the result(s) of the last \langle expression \rangle in the \langle clause \rangle is(are) returned as the result(s) of the entire `cond` expression. If the selected \langle clause \rangle contains only the \langle test \rangle and no \langle expression \rangle s, then the value of the \langle test \rangle is returned as the result. If the selected \langle clause \rangle uses the `=>` alternate form, then the \langle expression \rangle is evaluated. Its value must be a procedure that accepts one argument; this procedure is then called on the value of the \langle test \rangle and the value(s) returned by this procedure is(are) returned by the `cond` expression. If all \langle test \rangle s evaluate to false values, and there is no `else` clause, then the result of the conditional expression is unspecified; if there is an `else` clause, then its \langle expression \rangle s are evaluated, and the value(s) of the last one is(are) returned.

```
(cond ((> 3 2) 'greater)
      ((< 3 2) 'less))           => greater
(cond ((> 3 3) 'greater)
      ((< 3 3) 'less)
      (else 'equal))           => equal
(cond ((assv 'b '((a 1)(b 2))) => cadr)
      (else #f))               => 2
```

`(case <key> <clause1> <clause2> ...)` library syntax

Syntax: \langle Key \rangle may be any expression. Each \langle clause \rangle should have the form

```
((<datum1> ...) <expression1> <expression2> ...),
```

where each \langle datum \rangle is an external representation of some object. All the \langle datum \rangle s must be distinct. The last \langle clause \rangle may be an “else clause,” which has the form

```
(else <expression1> <expression2> ...).
```

Semantics: A `case` expression is evaluated as follows. \langle Key \rangle is evaluated and its result is compared against each \langle datum \rangle . If the result of evaluating \langle key \rangle is equivalent (in the sense of `equiv?`; see Section 7.1) to a \langle datum \rangle , then the expressions in the corresponding \langle clause \rangle are evaluated from left to right and the result(s) of the last expression in the \langle clause \rangle is(are) returned as the result(s) of the `case` expression. If the result of evaluating \langle key \rangle is different from every \langle datum \rangle , then if there is an `else` clause its expressions are evaluated and the result(s) of the last is(are) the result(s) of the `case` expression; otherwise the result of the `case` expression is unspecified.

```
(case (* 2 3)
      ((2 3 5 7) 'prime)
      ((1 4 6 8 9) 'composite)) => composite
```

```

(case (car '(c d))
  ((a) 'a)
  ((b) 'b))           ⇒ unspecified
(case (car '(c d))
  ((a e i o u)'vowel)
  ((w y) 'semivowel)
  (else 'consonant)) ⇒ consonant

```

(and <test₁> ...) library syntax

The <test> expressions are evaluated from left to right, and the value of the first expression that evaluates to a false value (see Section 7.3.1) is returned. Any remaining expressions are not evaluated. If all the expressions evaluate to true values, the value of the last expression is returned. If there are no expressions then #t is returned.

```

(and (= 2 2) (> 2 1)) ⇒ #t
(and (= 2 2) (< 2 1)) ⇒ #f
(and 1 2 'c '(f g))   ⇒ (f g)
(and)                  ⇒ #t

```

(or <test₁> ...) library syntax

The <test> expressions are evaluated from left to right, and the value of the first expression that evaluates to a true value (see Section 7.3.1) is returned. Any remaining expressions are not evaluated. If all expressions evaluate to false values, the value of the last expression is returned. If there are no expressions then #f is returned.

```

(or (= 2 2) (> 2 1)) ⇒ #t
(or (= 2 2) (< 2 1)) ⇒ #t
(or #f #f #f)        ⇒ #f
(or (memq 'b '(a b c))
    (/ 3 0))          ⇒ (b c)

```

5.2.2. Binding constructs. The three binding constructs `let`, `let*`, and `letrec` give Scheme a block structure, like Algol 60. The syntax of the three constructs is identical, but they differ in the regions they establish for their variable bindings. In a `let` expression, the initial values are computed before any of the variables become bound; in a `let*` expression, the bindings and evaluations are performed sequentially; while in a `letrec` expression, all the bindings are in effect while their initial values are being computed, thus allowing mutually recursive definitions.

(let (bindings) (body)) library syntax

Syntax: <Bindings> should have the form

```
((<variable1> <init1>) ...),
```

where each $\langle \text{init} \rangle$ is an expression, and $\langle \text{body} \rangle$ should be a sequence of one or more expressions. It is an error for a $\langle \text{variable} \rangle$ to appear more than once in the list of variables being bound.

Semantics: The $\langle \text{init} \rangle$ s are evaluated in the current environment (in some unspecified order), the $\langle \text{variable} \rangle$ s are bound to fresh locations holding the results, the $\langle \text{body} \rangle$ is evaluated in the extended environment, and the value(s) of the last expression of $\langle \text{body} \rangle$ is(are) returned. Each binding of a $\langle \text{variable} \rangle$ has $\langle \text{body} \rangle$ as its region.

$$\begin{array}{l} (\text{let } ((x \ 2) \ (y \ 3)) \\ \quad (* \ x \ y)) \end{array} \quad \Longrightarrow \quad 6$$

$$\begin{array}{l} (\text{let } ((x \ 2) \ (y \ 3)) \\ \quad (\text{let } ((x \ 7) \\ \quad \quad (z \ (+ \ x \ y))) \\ \quad \quad (* \ z \ x))) \end{array} \quad \Longrightarrow \quad 35$$

See also named `let`, Section 5.2.4.

`(let* <bindings> <body>)`

library syntax

Syntax: $\langle \text{Bindings} \rangle$ should have the form

$$((\langle \text{variable}_1 \rangle \langle \text{init}_1 \rangle) \dots),$$

and $\langle \text{body} \rangle$ should be a sequence of one or more expressions.

Semantics: `let*` is similar to `let`, but the bindings are performed sequentially from left to right, and the region of a binding indicated by $(\langle \text{variable} \rangle \langle \text{init} \rangle)$ is that part of the `let*` expression to the right of the binding. Thus the second binding is done in an environment in which the first binding is visible, and so on.

$$\begin{array}{l} (\text{let } ((x \ 2) \ (y \ 3)) \\ \quad (\text{let* } ((x \ 7) \\ \quad \quad (z \ (+ \ x \ y))) \\ \quad \quad (* \ z \ x))) \end{array} \quad \Longrightarrow \quad 70$$

`(letrec <bindings> <body>)`

library syntax

Syntax: $\langle \text{Bindings} \rangle$ should have the form

$$((\langle \text{variable}_1 \rangle \langle \text{init}_1 \rangle) \dots),$$

and $\langle \text{body} \rangle$ should be a sequence of one or more expressions. It is an error for a $\langle \text{variable} \rangle$ to appear more than once in the list of variables being bound.

Semantics: The $\langle \text{variable} \rangle$ s are bound to fresh locations holding undefined values, the $\langle \text{init} \rangle$ s are evaluated in the resulting environment (in some unspecified order), each $\langle \text{variable} \rangle$

is assigned to the result of the corresponding $\langle \text{init} \rangle$, the $\langle \text{body} \rangle$ is evaluated in the resulting environment, and the value(s) of the last expression in $\langle \text{body} \rangle$ is(are) returned. Each binding of a $\langle \text{variable} \rangle$ has the entire `letrec` expression as its region, making it possible to define mutually recursive procedures.

```
(letrec ((even?
         (lambda (n)
           (if (zero? n)
               #t
               (odd? (- n 1)))))
        (odd?
         (lambda (n)
           (if (zero? n)
               #f
               (even? (- n 1)))))
        (even? 88))) ⇒ #t
```

One restriction on `letrec` is very important: it must be possible to evaluate each $\langle \text{init} \rangle$ without assigning or referring to the value of any $\langle \text{variable} \rangle$. If this restriction is violated, then it is an error. The restriction is necessary because Scheme passes arguments by value rather than by name. In the most common uses of `letrec`, all the $\langle \text{init} \rangle$ s are lambda expressions and the restriction is satisfied automatically.

5.2.3. Sequencing.

```
(begin  $\langle \text{expression}_1 \rangle$   $\langle \text{expression}_2 \rangle$  ...) library syntax
```

The $\langle \text{expression} \rangle$ s are evaluated sequentially from left to right, and the value(s) of the last $\langle \text{expression} \rangle$ is(are) returned. This expression type is used to sequence side effects such as input and output.

```
(define x 0)

(begin (set! x 5)
       (+ x 1)) ⇒ 6

(begin (display "4 plus 1 equals ")
       (display (+ 4 1))) ⇒ unspecified
                          and prints 4 plus 1 equals 5
```

5.2.4. Iteration.

```
(do (( $\langle \text{variable}_1 \rangle$   $\langle \text{init}_1 \rangle$   $\langle \text{step}_1 \rangle$ )
     ...)
    (( $\langle \text{test} \rangle$   $\langle \text{expression} \rangle$  ...)
     ( $\langle \text{command} \rangle$  ...)) library syntax
```


5.2.5. *Delayed evaluation.*

(delay <expression>)

library syntax

The delay construct is used together with the procedure `force` to implement *lazy evaluation* or *call by need*. (delay <expression>) returns an object called a *promise* which at some point in the future may be asked (by the `force` procedure) to evaluate <expression>, and deliver the resulting value. The effect of <expression> returning multiple values is unspecified.

See the description of `force` (Section 7.4) for a more complete description of delay.

5.2.6. *Quasiquoteation.*

(quasiquote <qq template>)

syntax

`<qq template>

syntax

“Backquote” or “quasiquote” expressions are useful for constructing a list or vector structure when most but not all of the desired structure is known in advance. If no commas appear within the <qq template>, the result of evaluating `<qq template> is equivalent to the result of evaluating ’<qq template>. If a comma appears within the <qq template>, however, the expression following the comma is evaluated (“unquoted”) and its result is inserted into the structure instead of the comma and the expression. If a comma appears followed immediately by an at-sign, (@), then the following expression must evaluate to a list; the opening and closing parentheses of the list are then “stripped away” and the elements of the list are inserted in place of the comma at-sign expression sequence. A comma at-sign should only appear within a list or vector <qq template>.

```

`(list ,(+ 1 2) 4)           ⇒ (list 3 4)
(let ((name 'a)) `(list ,name ,name))
                          ⇒ (list a (quote a))
`(a ,(+ 1 2) ,@(map abs '(4 -5 6)) b)
                          ⇒ (a 3 4 5 6 b)
`((foo ,(- 10 3)),@(cdr '(c)) . ,(car '(cons)))
                          ⇒ ((foo 7) . cons)
`#(10 5 ,(sqrt 4) ,@(map sqrt '(16 9)) 8)
                          ⇒ #(10 5 2 4 3 8)

```

Quasiquote forms may be nested. Substitutions are made only for unquoted components appearing at the same nesting level as the outermost backquote. The nesting level increases by one inside each successive quasiquoteation, and decreases by one inside each unquoteation.

```

` (a ` (b , (+ 1 2) , (foo , (+ 1 3) d) e) f)
                                     ⇒ (a ` (b , (+ 1 2)
                                             , (foo 4 d) e) f)

(let ((name1 'x)
      (name2 'y))
  ` (a ` (b , ,name1 , ',name2 d) e)) ⇒ (a ` (b , x , 'y d) e)

```

The two notations ``(qq template)` and `(quasiquote (qq template))` are identical in all respects. `,(expression)` is identical to `(unquote (expression))`, and `,@(expression)` is identical to `(unquote-splicing (expression))`. The external syntax generated by `write` for two-element lists whose `car` is one of these symbols may vary between implementations.

```

(quasiquote (list (unquote (+ 1 2)) 4))
                                     ⇒ (list 3 4)
' (quasiquote (list (unquote (+ 1 2)) 4))
                                     ⇒ ` (list , (+ 1 2) 4)
                                     i.e., (quasiquote (list (unquote (+ 1 2)) 4))

```

Unpredictable behavior can result if any of the symbols `quasiquote`, `unquote`, or `unquote-splicing` appear in positions within a `(qq template)` otherwise than as described above.

5.3. *Macros*

Scheme programs can define and use new derived expression types, called *macros*. Program-defined expression types have the syntax

```
((keyword) (datum) ...)
```

where `(keyword)` is an identifier that uniquely determines the expression type. This identifier is called the *syntactic keyword*, or simply *keyword*, of the macro. The number of the `(datum)`s, and their syntax, depends on the expression type.

Each instance of a macro is called a *use* of the macro. The set of rules that specifies how a use of a macro is transcribed into a more primitive expression is called the *transformer* of the macro.

The macro definition facility consists of two parts:

- A set of expressions used to establish that certain identifiers are macro keywords, associate them with macro transformers, and control the scope within which a macro is defined, and
- a pattern language for specifying macro transformers.

The syntactic keyword of a macro may shadow variable bindings, and local variable bindings may shadow keyword bindings. All macros defined using the pattern language are “hygienic” and “referentially transparent” and thus preserve Scheme’s lexical scoping [2, 7, 9, 14, 15]:

- If a macro transformer inserts a binding for an identifier (variable or keyword), the identifier will in effect be renamed throughout its scope to avoid conflicts with other identifiers. Note that a `define` at top level may or may not introduce a binding; see Section 6.2.
- If a macro transformer inserts a free reference to an identifier, the reference refers to the binding that was visible where the transformer was specified, regardless of any local bindings that may surround the use of the macro.

5.3.1. Binding constructs for syntactic keywords. `let-syntax` and `letrec-syntax` are analogous to `let` and `letrec`, but they bind syntactic keywords to macro transformers instead of binding variables to locations that contain values. Syntactic keywords may also be bound at top level; see Section 6.3.

```
(let-syntax (bindings) (body)) syntax
```

Syntax: `<Bindings>` should have the form

```
((<keyword> <transformer spec>) ...)
```

Each `<keyword>` is an identifier, each `<transformer spec>` is an instance of `syntax-rules`, and `<body>` should be a sequence of one or more expressions. It is an error for a `<keyword>` to appear more than once in the list of keywords being bound.

Semantics: The `<body>` is expanded in the syntactic environment obtained by extending the syntactic environment of the `let-syntax` expression with macros whose keywords are the `<keyword>`s, bound to the specified transformers. Each binding of a `<keyword>` has `<body>` as its region.

```
(let-syntax ((when (syntax-rules ()
                  ((when test stmt1 stmt2 ...)
                   (if test
                       (begin stmt1
                              stmt2 ...))))))
  (let ((if #t))
    (when if (set! if 'now))
    if)) ⇒ now

(let ((x 'outer))
  (let-syntax ((m (syntax-rules () ((m)x))))
    (let ((x 'inner))
      (m)))) ⇒ outer
```

(letrec-syntax (bindings) (body))

syntax

Syntax: Same as for let-syntax.

Semantics: The (body) is expanded in the syntactic environment obtained by extending the syntactic environment of the letrec-syntax expression with macros whose keywords are the (keyword)s, bound to the specified transformers. Each binding of a (keyword) has the (bindings) as well as the (body) within its region, so the transformers can transcribe expressions into uses of the macros introduced by the letrec-syntax expression.

```
(letrec-syntax
  ((my-or (syntax-rules ()
           ((my-or) #f)
           ((my-or e) e)
           ((my-or e1 e2 ...)
            (let ((temp e1))
              (if temp
                  temp
                  (my-or e2 ...)))))))
  (let ((x #f)
        (y 7)
        (temp 8)
        (let odd?)
        (if even?))
    (my-or x
           (let temp)
           (if y)
           y)))           ⇒ 7
```

5.3.2. Pattern language. A (transformer spec) has the following form:

(syntax-rules (literals) (syntax rule) ...)

Syntax: (Literals) is a list of identifiers and each (syntax rule) should be of the form

((pattern) (template))

The (pattern) in a (syntax rule) is a list (pattern) that begins with the keyword for the macro.

A (pattern) is either an identifier, a constant, or one of the following

```
((pattern) ...)
((pattern) (pattern) ... (pattern))
((pattern) ... (pattern) (ellipsis))
#((pattern) ...)
#((pattern) ... (pattern) (ellipsis))
```

and a template is either an identifier, a constant, or one of the following

```
(element) ...
(element) (element) ... . (template)
#(element) ...
```

where an $\langle \text{element} \rangle$ is a $\langle \text{template} \rangle$ optionally followed by an $\langle \text{ellipsis} \rangle$ and an $\langle \text{ellipsis} \rangle$ is the identifier “...” (which cannot be used as an identifier in either a template or a pattern).

Semantics: An instance of `syntax-rules` produces a new macro transformer by specifying a sequence of hygienic rewrite rules. A use of a macro whose keyword is associated with a transformer specified by `syntax-rules` is matched against the patterns contained in the $\langle \text{syntax rule} \rangle$ s, beginning with the leftmost $\langle \text{syntax rule} \rangle$. When a match is found, the macro use is transcribed hygienically according to the template.

An identifier that appears in the pattern of a $\langle \text{syntax rule} \rangle$ is a *pattern variable*, unless it is the keyword that begins the pattern, is listed in $\langle \text{literals} \rangle$, or is the identifier “...”. Pattern variables match arbitrary input elements and are used to refer to elements of the input in the template. It is an error for the same pattern variable to appear more than once in a $\langle \text{pattern} \rangle$.

The keyword at the beginning of the pattern in a $\langle \text{syntax rule} \rangle$ is not involved in the matching and is not considered a pattern variable or literal identifier.

Rationale: The scope of the keyword is determined by the expression or syntax definition that binds it to the associated macro transformer. If the keyword were a pattern variable or literal identifier, then the template that follows the pattern would be within its scope regardless of whether the keyword were bound by `let-syntax` or by `letrec-syntax`.

Identifiers that appear in $\langle \text{literals} \rangle$ are interpreted as literal identifiers to be matched against corresponding subforms of the input. A subform in the input matches a literal identifier if and only if it is an identifier and either both its occurrence in the macro expression and its occurrence in the macro definition have the same lexical binding, or the two identifiers are equal and both have no lexical binding.

A subpattern followed by ... can match zero or more elements of the input. It is an error for ... to appear in $\langle \text{literals} \rangle$. Within a pattern the identifier ... must follow the last element of a nonempty sequence of subpatterns.

More formally, an input form F matches a pattern P if and only if:

- P is a non-literal identifier; or
- P is a literal identifier and F is an identifier with the same binding; or
- P is a list $(P_1 \dots P_n)$ and F is a list of n forms that match P_1 through P_n , respectively; or
- P is an improper list $(P_1 P_2 \dots P_n . P_{n+1})$ and F is a list or improper list of n or more forms that match P_1 through P_n , respectively, and whose n th “cdr” matches P_{n+1} ; or
- P is of the form $(P_1 \dots P_n P_{n+1} \langle \text{ellipsis} \rangle)$ where $\langle \text{ellipsis} \rangle$ is the identifier ... and F is a proper list of at least n forms, the first n of which match P_1 through P_n , respectively, and each remaining element of F matches P_{n+1} ; or

- P is a vector of the form $\#(P_1 \dots P_n)$ and F is a vector of n forms that match P_1 through P_n ; or
- P is of the form $\#(P_1 \dots P_n P_{n+1} \langle \text{ellipsis} \rangle)$ where $\langle \text{ellipsis} \rangle$ is the identifier \dots and F is a vector of n or more forms the first n of which match P_1 through P_n , respectively, and each remaining element of F matches P_{n+1} ; or
- P is a datum and F is equal to P in the sense of the `equal?` procedure.

It is an error to use a macro keyword, within the scope of its binding, in an expression that does not match any of the patterns.

When a macro use is transcribed according to the template of the matching $\langle \text{syntax rule} \rangle$, pattern variables that occur in the template are replaced by the subforms they match in the input. Pattern variables that occur in subpatterns followed by one or more instances of the identifier \dots are allowed only in subtemplates that are followed by as many instances of \dots . They are replaced in the output by all of the subforms they match in the input, distributed as indicated. It is an error if the output cannot be built up as specified.

Identifiers that appear in the template but are not pattern variables or the identifier \dots are inserted into the output as literal identifiers. If a literal identifier is inserted as a free identifier then it refers to the binding of that identifier within whose scope the instance of `syntax-rules` appears. If a literal identifier is inserted as a bound identifier then it is in effect renamed to prevent inadvertent captures of free identifiers.

As an example, if `let` and `cond` are defined as in Section 8.3 then they are hygienic (as required) and the following is not an error.

```
(let ((=> #f))
  (cond (#t => 'ok)))           ==> ok
```

The macro transformer for `cond` recognizes `=>` as a local variable, and hence an expression, and not as the top-level identifier `=>`, which the macro transformer treats as a syntactic keyword. Thus the example expands into

```
(let ((=> #f))
  (if #t (begin => 'ok)))
```

instead of

```
(let ((=> #f))
  (let ((temp #t))
    (if temp ('ok temp))))
```

which would result in an invalid procedure call.

6. Program structure

6.1. Programs

A Scheme program consists of a sequence of expressions, definitions, and syntax definitions. Expressions are described in Section 5; definitions and syntax definitions are the subject of the rest of the present section.

Programs are typically stored in files or entered interactively to a running Scheme system, although other paradigms are possible; questions of user interface lie outside the scope of this report. (Indeed, Scheme would still be useful as a notation for expressing computational methods even in the absence of a mechanical implementation.)

Definitions and syntax definitions occurring at the top level of a program can be interpreted declaratively. They cause bindings to be created in the top level environment or modify the value of existing top-level bindings. Expressions occurring at the top level of a program are interpreted imperatively; they are executed in order when the program is invoked or loaded, and typically perform some kind of initialization.

At the top level of a program (`begin` $\langle\text{form}_1\rangle \dots$) is equivalent to the sequence of expressions, definitions, and syntax definitions that form the body of the `begin`.

6.2. Definitions

Definitions are valid in some, but not all, contexts where expressions are allowed. They are valid only at the top level of a $\langle\text{program}\rangle$ and at the beginning of a $\langle\text{body}\rangle$.

A definition should have one of the following forms:

- `(define` $\langle\text{variable}\rangle$ $\langle\text{expression}\rangle$)
- `(define` ($\langle\text{variable}\rangle$ $\langle\text{formals}\rangle$) $\langle\text{body}\rangle$)

$\langle\text{Formals}\rangle$ should be either a sequence of zero or more variables, or a sequence of one or more variables followed by a space-delimited period and another variable (as in a lambda expression). This form is equivalent to

```
(define  $\langle\text{variable}\rangle$ 
  (lambda ( $\langle\text{formals}\rangle$ )  $\langle\text{body}\rangle$ )).
```

- `(define` ($\langle\text{variable}\rangle$. $\langle\text{formals}\rangle$) $\langle\text{body}\rangle$)
- $\langle\text{Formals}\rangle$ should be a single variable. This form is equivalent to

```
(define  $\langle\text{variable}\rangle$ 
  (lambda ( $\langle\text{formal}\rangle$ )  $\langle\text{body}\rangle$ )).
```

6.2.1. Top level definitions. At the top level of a program, a definition

```
(define  $\langle\text{variable}\rangle$   $\langle\text{expression}\rangle$ )
```

has essentially the same effect as the assignment expression

```
(set!  $\langle\text{variable}\rangle$   $\langle\text{expression}\rangle$ )
```

if $\langle\text{variable}\rangle$ is bound. If $\langle\text{variable}\rangle$ is not bound, however, then the definition will bind $\langle\text{variable}\rangle$ to a new location before performing the assignment, whereas it would be an error to perform a `set!` on an unbound variable.

```

(define add3
  (lambda (x) (+ x 3)))
(add3 3)                                $\implies$  6
(define first car)
(first '(1 2))                           $\implies$  1

```

Some implementations of Scheme use an initial environment in which all possible variables are bound to locations, most of which contain undefined values. Top level definitions in such an implementation are truly equivalent to assignments.

6.2.2. Internal definitions. Definitions may occur at the beginning of a \langle body \rangle (that is, the body of a lambda, let, let*, letrec, let-syntax, or letrec-syntax expression or that of a definition of an appropriate form). Such definitions are known as *internal definitions* as opposed to the top level definitions described above. The variable defined by an internal definition is local to the \langle body \rangle . That is, \langle variable \rangle is bound rather than assigned, and the region of the binding is the entire \langle body \rangle . For example,

```

(let ((x 5))
  (define foo (lambda (y) (bar x y)))
  (define bar (lambda (a b) (+ (* a b) a)))
  (foo (+ x 3)))                        $\implies$  45

```

A \langle body \rangle containing internal definitions can always be converted into a completely equivalent letrec expression. For example, the let expression in the above example is equivalent to

```

(let ((x 5))
  (letrec ((foo (lambda (y) (bar x y)))
           (bar (lambda (a b) (+ (* a b) a))))
    (foo (+ x 3))))

```

Just as for the equivalent letrec expression, it must be possible to evaluate each \langle expression \rangle of every internal definition in a \langle body \rangle without assigning or referring to the value of any \langle variable \rangle being defined.

Wherever an internal definition may occur ($\text{begin } \langle$ definition $_1\rangle \dots$) is equivalent to the sequence of definitions that form the body of the begin.

6.3. Syntax definitions

Syntax definitions are valid only at the top level of a \langle program \rangle . They have the following form:

```
(define-syntax  $\langle$ keyword $\rangle$   $\langle$ transformer spec $\rangle$ )
```

`<keyword>` is an identifier, and the `<transformer spec>` should be an instance of `syntax-rules`. The top-level syntactic environment is extended by binding the `<keyword>` to the specified transformer.

There is no `define-syntax` analogue of internal definitions.

Although macros may expand into definitions and syntax definitions in any context that permits them, it is an error for a definition or syntax definition to shadow a syntactic keyword whose meaning is needed to determine whether some form in the group of forms that contains the shadowing definition is in fact a definition, or, for internal definitions, is needed to determine the boundary between the group and the expressions that follow the group. For example, the following are errors:

```
(define define 3)

(begin (define begin list))

(let-syntax
  ((foo (syntax-rules ()
         ((foo (proc args ...) body ...)
          (define proc
            (lambda (args ...)
              body ...))))))
  (let ((x 3))
    (foo (plus x y) (+ x y))
    (define foo x)
    (plus foo x)))
```

7. Standard procedures

This section describes Scheme's built-in procedures. The initial (or "top level") Scheme environment starts out with a number of variables bound to locations containing useful values, most of which are primitive procedures that manipulate data. For example, the variable `abs` is bound to (a location initially containing) a procedure of one argument that computes the absolute value of a number, and the variable `+` is bound to a procedure that computes sums. Built-in procedures that can easily be written in terms of other built-in procedures are identified as "library procedures".

A program may use a top-level definition to bind any variable. It may subsequently alter any such binding by an assignment (see Section 5.1.6). These operations do not modify the behavior of Scheme's built-in procedures. Altering any top-level binding that has not been introduced by a definition has an unspecified effect on the behavior of the built-in procedures.

7.1. Equivalence predicates

A *predicate* is a procedure that always returns a boolean value (`#t` or `#f`). An *equivalence predicate* is the computational analogue of a mathematical equivalence relation (it is symmetric, reflexive, and transitive). Of the equivalence predicates described in this section,

`eq?` is the finest or most discriminating, and `equal?` is the coarsest. `Eqv?` is slightly less discriminating than `eq?`.

`(eqv? obj1 obj2)`

procedure

The `eqv?` procedure defines a useful equivalence relation on objects. Briefly, it returns `#t` if `obj1` and `obj2` should normally be regarded as the same object. This relation is left slightly open to interpretation, but the following partial specification of `eqv?` holds for all implementations of Scheme.

The `eqv?` procedure returns `#t` if:

- `obj1` and `obj2` are both `#t` or both `#f`.
- `obj1` and `obj2` are both symbols and

$$\begin{aligned} &(\text{string=?} (\text{symbol}\rightarrow\text{string } obj_1) \\ & \quad (\text{symbol}\rightarrow\text{string } obj_2)) \implies \#t \end{aligned}$$

Note: This assumes that neither `obj1` nor `obj2` is an “uninterned symbol” as alluded to in Section 7.3.3. This report does not presume to specify the behavior of `eqv?` on implementation-dependent extensions.

- `obj1` and `obj2` are both numbers, are numerically equal (see `=`, Section 7.2), and are either both exact or both inexact.
- `obj1` and `obj2` are both characters and are the same character according to the `char=?` procedure (Section 7.3.4).
- both `obj1` and `obj2` are the empty list.
- `obj1` and `obj2` are pairs, vectors, or strings that denote the same locations in the store (Section 4.4).
- `obj1` and `obj2` are procedures whose location tags are equal (Section 5.1.4).

The `eqv?` procedure returns `#f` if:

- `obj1` and `obj2` are of different types (Section 4.2).
- one of `obj1` and `obj2` is `#t` but the other is `#f`.
- `obj1` and `obj2` are symbols but

$$\begin{aligned} &(\text{string=?} (\text{symbol}\rightarrow\text{string } obj_1) \\ & \quad (\text{symbol}\rightarrow\text{string } obj_2)) \implies \#f \end{aligned}$$

- one of `obj1` and `obj2` is an exact number but the other is an inexact number.
- `obj1` and `obj2` are numbers for which the `=` procedure returns `#f`.
- `obj1` and `obj2` are characters for which the `char=?` procedure returns `#f`.
- one of `obj1` and `obj2` is the empty list but the other is not.
- `obj1` and `obj2` are pairs, vectors, or strings that denote distinct locations.

- obj_1 and obj_2 are procedures that would behave differently (return different value(s) or have different side effects) for some arguments.

```

(eqv? 'a 'a)           ⇒ #t
(eqv? 'a 'b)           ⇒ #f
(eqv? 2 2)             ⇒ #t
(eqv? '() '())         ⇒ #t
(eqv? 100000000 100000000) ⇒ #t
(eqv? (cons 1 2) (cons 1 2)) ⇒ #f
(eqv? (lambda () 1)
      (lambda () 2))   ⇒ #f
(eqv? #f 'nil)         ⇒ #f
(let ((p (lambda (x) x)))
  (eqv? p p))          ⇒ #t

```

The following examples illustrate cases in which the above rules do not fully specify the behavior of `eqv?`. All that can be said about such cases is that the value returned by `eqv?` must be a boolean.

```

(eqv? "" "")           ⇒ unspecified
(eqv? '#() '#())      ⇒ unspecified
(eqv? (lambda (x) x)
      (lambda (x) x)) ⇒ unspecified
(eqv? (lambda (x) x)
      (lambda (y) y)) ⇒ unspecified

```

The next set of examples shows the use of `eqv?` with procedures that have local state. `Gen-counter` must return a distinct procedure every time, since each procedure has its own internal counter. `Gen-loser`, however, returns equivalent procedures each time, since the local state does not affect the value or side effects of the procedures.

```

(define gen-counter
  (lambda ()
    (let ((n 0))
      (lambda () (set! n (+ n 1)) n))))
(let ((g (gen-counter)))
  (eqv? g g) ⇒ #t
  (eqv? (gen-counter) (gen-counter)) ⇒ #f
  (define gen-loser
    (lambda ()
      (let ((n 0))
        (lambda () (set! n (+ n 1)) 27))))
  (let ((g (gen-loser)))
    (eqv? g g) ⇒ #t
    (eqv? (gen-loser) (gen-loser)) ⇒ unspecified

```

```

(letrec ((f (lambda () (if (eqv? f g) 'both 'f)))
         (g (lambda () (if (eqv? f g) 'both 'g))))
  (eqv? f g))           ⇒ unspecified
(letrec ((f (lambda () (if (eqv? f g) 'f 'both)))
         (g (lambda () (if (eqv? f g) 'g 'both))))
  (eqv? f g))           ⇒ #f

```

Since it is an error to modify constant objects (those returned by literal expressions), implementations are permitted, though not required, to share structure between constants where appropriate. Thus the value of `eqv?` on constants is sometimes implementation-dependent.

```

(eqv? '(a) '(a))           ⇒ unspecified
(eqv? "a" "a")             ⇒ unspecified
(eqv? '(b) (cdr '(a b)))   ⇒ unspecified
(let ((x '(a)))
  (eqv? x x))               ⇒ #t

```

Rationale: The above definition of `eqv?` allows implementations latitude in their treatment of procedures and literals: implementations are free either to detect or to fail to detect that two procedures or two literals are equivalent to each other, and can decide whether or not to merge representations of equivalent objects by using the same pointer or bit pattern to represent both.

`(eq? obj1 obj2)` procedure

`Eq?` is similar to `eqv?` except that in some cases it is capable of discerning distinctions finer than those detectable by `eqv?`.

`Eq?` and `eqv?` are guaranteed to have the same behavior on symbols, booleans, the empty list, pairs, procedures, and nonempty strings and vectors. `Eq?`'s behavior on numbers and characters is implementation-dependent, but it will always return either true or false, and will return true only when `eqv?` would also return true. `Eq?` may also behave differently from `eqv?` on empty vectors and empty strings.

```

(eq? 'a 'a)                 ⇒ #t
(eq? '(a) '(a))             ⇒ unspecified
(eq? (list 'a) (list 'a))   ⇒ #f
(eq? "a" "a")               ⇒ unspecified
(eq? "" "")                 ⇒ unspecified
(eq? '() '())               ⇒ #t
(eq? 2 2)                   ⇒ unspecified
(eq? #\A #\A)               ⇒ unspecified
(eq? car car)               ⇒ #t
(let ((n (+2 3)))
  (eq? n n))                 ⇒ unspecified
(let ((x '(a)))
  (eq? x x))                 ⇒ unspecified

```

```

(eq? x x)           ⇒ #t
(let ((x '#()))
  (eq? x x))       ⇒ #t
(let ((p (lambda (x) x)))
  (eq? p p))       ⇒ #t

```

Rationale: It will usually be possible to implement `eq?` much more efficiently than `eqv?`, for example, as a simple pointer comparison instead of as some more complicated operation. One reason is that it may not be possible to compute `eqv?` of two numbers in constant time, whereas `eq?` implemented as pointer comparison will always finish in constant time. `Eq?` may be used like `eqv?` in applications using procedures to implement objects with state since it obeys the same constraints as `eqv?`.

`(equal? obj1 obj2)` library procedure

`Equal?` recursively compares the contents of pairs, vectors, and strings, applying `eqv?` on other objects such as numbers and symbols. A rule of thumb is that objects are generally `equal?` if they print the same. `Equal?` may fail to terminate if its arguments are circular data structures.

```

(equal? 'a 'a)           ⇒ #t
(equal? '(a) '(a))      ⇒ #t
(equal? '(a (b) c)
         '(a (b) c))    ⇒ #t
(equal? "abc" "abc")    ⇒ #t
(equal? 2 2)            ⇒ #t
(equal? (make-vector 5 'a)
         (make-vector 5 'a)) ⇒ #t
(equal? (lambda (x) x)
         (lambda (y) y)) ⇒ unspecified

```

7.2. Numbers

Numerical computation has traditionally been neglected by the Lisp community. Until Common Lisp there was no carefully thought out strategy for organizing numerical computation, and with the exception of the MacLisp system [20] little effort was made to execute numerical code efficiently. This report recognizes the excellent work of the Common Lisp committee and accepts many of their recommendations. In some ways this report simplifies and generalizes their proposals in a manner consistent with the purposes of Scheme.

It is important to distinguish between the mathematical numbers, the Scheme numbers that attempt to model them, the machine representations used to implement the Scheme numbers, and notations used to write numbers. This report uses the types *number*, *complex*, *real*, *rational*, and *integer* to refer to both mathematical numbers and Scheme numbers.

Machine representations such as fixed point and floating point are referred to by names such as *fixnum* and *flonum*.

7.2.1. Numerical types. Mathematically, numbers may be arranged into a tower of subtypes in which each level is a subset of the level above it:

- number
- complex
- real
- rational
- integer

For example, 3 is an integer. Therefore, 3 is also a rational, a real, and a complex. The same is true of the Scheme numbers that model 3. For Scheme numbers, these types are defined by the predicates `number?`, `complex?`, `real?`, `rational?`, and `integer?`.

There is no simple relationship between a number's type and its representation inside a computer. Although most implementations of Scheme will offer at least two different representations of 3, these different representations denote the same integer.

Scheme's numerical operations treat numbers as abstract data, as independent of their representation as possible. Although an implementation of Scheme may use `fixnum`, `flonum`, and perhaps other representations for numbers, this should not be apparent to a casual programmer writing simple programs.

It is necessary, however, to distinguish between numbers that are represented exactly and those that may not be. For example, indexes into data structures must be known exactly, as must some polynomial coefficients in a symbolic algebra system. On the other hand, the results of measurements are inherently inexact, and irrational numbers may be approximated by rational and therefore inexact approximations. In order to catch uses of inexact numbers where exact numbers are required, Scheme explicitly distinguishes exact from inexact numbers. This distinction is orthogonal to the dimension of type.

7.2.2. Exactness. Scheme numbers are either *exact* or *inexact*. A number is exact if it was written as an exact constant or was derived from exact numbers using only exact operations. A number is inexact if it was written as an inexact constant, if it was derived using inexact ingredients, or if it was derived using inexact operations. Thus inexactness is a contagious property of a number.

If two implementations produce exact results for a computation that did not involve inexact intermediate results, the two ultimate results will be mathematically equivalent. This is generally not true of computations involving inexact numbers since approximate methods such as floating point arithmetic may be used, but it is the duty of each implementation to make the result as close as practical to the mathematically ideal result.

Rational operations such as `+` should always produce exact results when given exact arguments. If the operation is unable to produce an exact result, then it may either report the violation of an implementation restriction or it may silently coerce its result to an inexact value. See Section 7.2.3.

With the exception of `inexact->exact`, the operations described in this section must generally return `inexact` results when given any `inexact` arguments. An operation may, however, return an `exact` result if it can prove that the value of the result is unaffected by the `inexactness` of its arguments. For example, multiplication of any number by an `exact zero` may produce an `exact zero` result, even if the other argument is `inexact`.

7.2.3. Implementation restrictions. Implementations of Scheme are not required to implement the whole tower of subtypes given in Section 7.2.1, but they must implement a coherent subset consistent with both the purposes of the implementation and the spirit of the Scheme language. For example, an implementation in which all numbers are real may still be quite useful.

Implementations may also support only a limited range of numbers of any type, subject to the requirements of this section. The supported range for `exact` numbers of any type may be different from the supported range for `inexact` numbers of that type. For example, an implementation that uses `flonums` to represent all its `inexact` real numbers may support a practically unbounded range of `exact` integers and rationals while limiting the range of `inexact` reals (and therefore the range of `inexact` integers and rationals) to the dynamic range of the `flonum` format. Furthermore the gaps between the representable `inexact` integers and rationals are likely to be very large in such an implementation as the limits of this range are approached.

An implementation of Scheme must support `exact` integers throughout the range of numbers that may be used for indexes of lists, vectors, and strings or that may result from computing the length of a list, vector, or string. The `length`, `vector-length`, and `string-length` procedures must return an `exact` integer, and it is an error to use anything but an `exact` integer as an index. Furthermore, any integer constant within the index range, if expressed by an `exact` integer syntax, will indeed be read as an `exact` integer, regardless of any implementation restrictions that may apply outside this range. Finally, the procedures listed below will always return an `exact` integer result provided all their arguments are `exact` integers and the mathematically expected result is representable as an `exact` integer within the implementation:

<code>+</code>	<code>-</code>	<code>*</code>
<code>quotient</code>	<code>remainder</code>	<code>modulo</code>
<code>max</code>	<code>min</code>	<code>abs</code>
<code>numerator</code>	<code>denominator</code>	<code>gcd</code>
<code>lcm</code>	<code>floor</code>	<code>ceiling</code>
<code>truncate</code>	<code>round</code>	<code>rationalize</code>
<code>expt</code>		

Implementations are encouraged, but not required, to support `exact` integers and `exact` rationals of practically unlimited size and precision, and to implement the above procedures and the `/` procedure in such a way that they always return `exact` results when given `exact` arguments. If one of these procedures is unable to deliver an `exact` result when given `exact` arguments, then it may either report a violation of an implementation restriction or it may silently coerce its result to an `inexact` number. Such a coercion may cause an error later.

An implementation may use floating point and other approximate representation strategies for inexact numbers. This report recommends, but does not require, that the IEEE 32-bit and 64-bit floating point standards be followed by implementations that use flonum representations, and that implementations using other representations should match or exceed the precision achievable using these floating point standards [12].

In particular, implementations that use flonum representations must follow these rules: A flonum result must be represented with at least as much precision as is used to express any of the inexact arguments to that operation. It is desirable (but not required) for potentially inexact operations such as `sqrt`, when applied to exact arguments, to produce exact answers whenever possible (for example the square root of an exact 4 ought to be an exact 2). If, however, an exact number is operated upon so as to produce an inexact result (as by `sqrt`), and if the result is represented as a flonum, then the most precise flonum format available must be used; but if the result is represented in some other way then the representation must have at least as much precision as the most precise flonum format available.

Although Scheme allows a variety of written notations for numbers, any particular implementation may support only some of them. For example, an implementation in which all numbers are real need not support the rectangular and polar notations for complex numbers. If an implementation encounters an exact numerical constant that it cannot represent as an exact number, then it may either report a violation of an implementation restriction or it may silently represent the constant by an inexact number.

7.2.4. Syntax of numerical constants. The syntax of the written representations for numbers is described formally in Section 8.1.1. Note that case is not significant in numerical constants.

A number may be written in binary, octal, decimal, or hexadecimal by the use of a radix prefix. The radix prefixes are `#b` (binary), `#o` (octal), `#d` (decimal), and `#x` (hexadecimal). With no radix prefix, a number is assumed to be expressed in decimal.

A numerical constant may be specified to be either exact or inexact by a prefix. The prefixes are `#e` for exact, and `#i` for inexact. An exactness prefix may appear before or after any radix prefix that is used. If the written representation of a number has no exactness prefix, the constant may be either inexact or exact. It is inexact if it contains a decimal point, an exponent, or a “#” character in the place of a digit, otherwise it is exact.

In systems with inexact numbers of varying precisions it may be useful to specify the precision of a constant. For this purpose, numerical constants may be written with an exponent marker that indicates the desired precision of the inexact representation. The letters `s`, `f`, `d`, and `l` specify the use of *short*, *single*, *double*, and *long* precision, respectively. (When fewer than four internal inexact representations exist, the four size specifications are mapped onto those available. For example, an implementation with two internal representations may map *short* and *single* together and *long* and *double* together.) In addition, the exponent marker `e` specifies the default precision for the implementation. The default precision has at least as much precision as *double*, but implementations may wish to allow this default to be set by the user.

3.14159265358979F0

Round to single — 3.141593

0.6L0

Extend to long — .6000000000000000

7.2.5. Numerical operations. The reader is referred to Section 2.3.3 for a summary of the naming conventions used to specify restrictions on the types of arguments to numerical routines. The examples used in this section assume that any numerical constant written using an exact notation is indeed represented as an exact number. Some examples also assume that certain numerical constants written using an inexact notation can be represented without loss of accuracy; the inexact constants were chosen so that this is likely to be true in implementations that use flonums to represent inexact numbers.

(number? <i>obj</i>)	procedure
(complex? <i>obj</i>)	procedure
(real? <i>obj</i>)	procedure
(rational? <i>obj</i>)	procedure
(integer? <i>obj</i>)	procedure

These numerical type predicates can be applied to any kind of argument, including non-numbers. They return #t if the object is of the named type, and otherwise they return #f. In general, if a type predicate is true of a number then all higher type predicates are also true of that number. Consequently, if a type predicate is false of a number, then all lower type predicates are also false of that number.

If z is an inexact complex number, then (real? z) is true if and only if (zero? (imag-part z)) is true. If x is an inexact real number, then (integer? x) is true if and only if ($= x$ (round x)).

(complex? 3+4i)	⇒	#t
(complex? 3)	⇒	#t
(real? 3)	⇒	#t
(real? -2.5+0.0i)	⇒	#t
(real? #e1e10)	⇒	#t
(rational? 6/10)	⇒	#t
(rational? 6/3)	⇒	#t
(integer? 3+0i)	⇒	#t
(integer? 3.0)	⇒	#t
(integer? 8/4)	⇒	#t

Note: The behavior of these type predicates on inexact numbers is unreliable, since any inaccuracy may affect the result.

Note: In many implementations the rational? procedure will be the same as real?, and the complex? procedure will be the same as number?, but unusual implementations may be able to represent some irrational numbers exactly or may extend the number system to support some kind of noncomplex numbers.

(exact? z)	procedure
(inexact? z)	procedure

These numerical predicates provide tests for the exactness of a quantity. For any Scheme number, precisely one of these predicates is true.

(= $z_1 z_2 z_3 \dots$)	procedure
(< $x_1 x_2 x_3 \dots$)	procedure
(> $x_1 x_2 x_3 \dots$)	procedure
(<= $x_1 x_2 x_3 \dots$)	procedure
(>= $x_1 x_2 x_3 \dots$)	procedure

These procedures return #t if their arguments are (respectively): equal, monotonically increasing, monotonically decreasing, monotonically nondecreasing, or monotonically non-increasing.

These predicates are required to be transitive.

Note: The traditional implementations of these predicates in Lisp-like languages are not transitive.

Note: While it is not an error to compare inexact numbers using these predicates, the results may be unreliable because a small inaccuracy may affect the result; this is especially true of = and zero?. When in doubt, consult a numerical analyst.

(zero? z)	library procedure
(positive? x)	library procedure
(negative? x)	library procedure
(odd? n)	library procedure
(even? n)	library procedure

These numerical predicates test a number for a particular property, returning #t or #f. See note above.

(max $x_1 x_2 \dots$)	library procedure
(min $x_1 x_2 \dots$)	library procedure

These procedures return the maximum or minimum of their arguments.

(max 3 4)	⇒ 4 ; exact
(max 3.9 4)	⇒ 4.0 ; inexact

Note: If any argument is inexact, then the result will also be inexact (unless the procedure can prove that the inaccuracy is not large enough to affect the result, which is possible only in unusual implementations). If min or max is used to compare numbers of mixed exactness, and the numerical value of the result cannot be represented as an inexact number

without loss of accuracy, then the procedure may report a violation of an implementation restriction.

(+ z_1 ...) procedure
 (* z_1 ...) procedure

These procedures return the sum or product of their arguments.

(+ 3 4) \implies 7
 (+ 3) \implies 3
 (+) \implies 0
 (* 4) \implies 4
 (*) \implies 1

(- z_1 z_2) procedure
 (- z) procedure
 (- z_1 z_2 ...) optional procedure
 (/ z_1 z_2) procedure
 (/ z) procedure
 (/ z_1 z_2 ...) optional procedure

With two or more arguments, these procedures return the difference or quotient of their arguments, associating to the left. With one argument, however, they return the additive or multiplicative inverse of their argument.

(- 3 4) \implies -1
 (- 3 4 5) \implies -6
 (- 3) \implies -3
 (/ 3 4 5) \implies 3/20
 (/ 3) \implies 1/3

(abs x) library procedure

Abs returns the absolute value of its argument.

(abs -7) \implies 7

(quotient n_1 n_2) procedure
 (remainder n_1 n_2) procedure
 (modulo n_1 n_2) procedure

These procedures implement number-theoretic (integer) division. n_2 should be nonzero. All three procedures return integers. If n_1/n_2 is an integer:

```
(quotient  $n_1$   $n_2$ )            $\implies$   $n_1/n_2$ 
(remainder  $n_1$   $n_2$ )          $\implies$  0
(modulo  $n_1$   $n_2$ )              $\implies$  0
```

If n_1/n_2 is not an integer:

```
(quotient  $n_1$   $n_2$ )            $\implies$   $n_q$ 
(remainder  $n_1$   $n_2$ )          $\implies$   $n_r$ 
(modulo  $n_1$   $n_2$ )              $\implies$   $n_m$ 
```

where n_q is n_1/n_2 rounded towards zero, $0 < |n_r| < |n_2|$, $0 < |n_m| < |n_2|$, n_r and n_m differ from n_1 by a multiple of n_2 , n_r has the same sign as n_1 , and n_m has the same sign as n_2 .

From this we can conclude that for integers n_1 and n_2 with n_2 not equal to 0,

```
(=  $n_1$  (+ (*  $n_2$  (quotient  $n_1$   $n_2$ ))
           (remainder  $n_1$   $n_2$ )))  $\implies$  #t
```

provided all numbers involved in that computation are exact.

```
(modulo 13 4)            $\implies$  1
(remainder 13 4)        $\implies$  1
```

```
(modulo -13 4)           $\implies$  3
(remainder -13 4)       $\implies$  -1
```

```
(modulo 13 -4)           $\implies$  -3
(remainder 13 -4)       $\implies$  1
```

```
(modulo -13 -4)          $\implies$  -1
(remainder -13 -4)      $\implies$  -1
```

```
(remainder -13 -4.0)     $\implies$  -1.0 ; inexact
```

```
(gcd  $n_1$  ...)           library procedure
(lcm  $n_1$  ...)           library procedure
```

These procedures return the greatest common divisor or least common multiple of their arguments. The result is always nonnegative.

```
(gcd 32 -36)            $\implies$  4
(gcd)                   $\implies$  0
(lcm 32 -36)            $\implies$  288
(lcm 32.0 -36)          $\implies$  288.0 ; inexact
(lcm)                   $\implies$  1
```

<code>(numerator q)</code>	procedure
<code>(denominator q)</code>	procedure

These procedures return the numerator or denominator of their argument; the result is computed as if the argument was represented as a fraction in lowest terms. The denominator is always positive. The denominator of 0 is defined to be 1.

```
(numerator (/ 6 4))      => 3
(denominator (/ 6 4))   => 2
(denominator
 (exact->inexact (/ 6 4))) => 2.0
```

<code>(floor x)</code>	procedure
<code>(ceiling x)</code>	procedure
<code>(truncate x)</code>	procedure
<code>(round x)</code>	procedure

These procedures return integers. `Floor` returns the largest integer not larger than x . `Ceiling` returns the smallest integer not smaller than x . `Truncate` returns the integer closest to x whose absolute value is not larger than the absolute value of x . `Round` returns the closest integer to x , rounding to even when x is halfway between two integers.

Rationale: `Round` rounds to even for consistency with the default rounding mode specified by the IEEE floating point standard.

Note: If the argument to one of these procedures is `inexact`, then the result will also be `inexact`. If an exact value is needed, the result should be passed to the `inexact->exact` procedure.

```
(floor -4.3)      => -5.0
(ceiling -4.3)   => -4.0
(truncate -4.3)  => -4.0
(round -4.3)     => -4.0

(floor 3.5)      => 3.0
(ceiling 3.5)   => 4.0
(truncate 3.5)  => 3.0
(round 3.5)     => 4.0 ; inexact

(round 7/2)      => 4    ; exact
(round 7)        => 7
```

<code>(rationalize x y)</code>	library procedure
--	-------------------

Rationalize returns the *simplest* rational number differing from x by no more than y . A rational number r_1 is *simpler* than another rational number r_2 if $r_1 = p_1/q_1$ and $r_2 = p_2/q_2$ (in lowest terms) and $|p_1| \leq |p_2|$ and $|q_1| \leq |q_2|$. Thus $3/5$ is simpler than $4/7$. Although not all rationals are comparable in this ordering (consider $2/7$ and $3/5$) any interval contains a rational number that is simpler than every other rational number in that interval (the simpler $2/5$ lies between $2/7$ and $3/5$). Note that $0 = 0/1$ is the simplest rational of all.

```
(rationalize
  (inexact->exact .3) 1/10)    => 1/3 ; exact
(rationalize .3 1/10)          => #i1/3 ; inexact
```

(exp z)	procedure
(log z)	procedure
(sin z)	procedure
(cos z)	procedure
(tan z)	procedure
(asin z)	procedure
(acos z)	procedure
(atan z)	procedure
(atan y x)	procedure

These procedures are part of every implementation that supports general real numbers; they compute the usual transcendental functions. Log computes the natural logarithm of z (not the base ten logarithm). Asin, acos, and atan compute arcsine (\sin^{-1}), arccosine (\cos^{-1}), and arctangent (\tan^{-1}), respectively. The two-argument variant of atan computes (angle (make-rectangular x y)) (see below), even in implementations that do not support general complex numbers.

In general, the mathematical functions log, arcsine, arccosine, and arctangent are multiply defined. The value of $\log z$ is defined to be the one whose imaginary part lies in the range from $-\pi$ (exclusive) to π (inclusive). $\log 0$ is undefined. With log defined this way, the values of $\sin^{-1} z$, $\cos^{-1} z$, and $\tan^{-1} z$ are according to the following formulae:

$$\begin{aligned} \sin^{-1} z &= -i \log(iz + \sqrt{1 - z^2}) \\ \cos^{-1} z &= \pi/2 - \sin^{-1} z \\ \tan^{-1} z &= (\log(1 + iz) - \log(1 - iz))/(2i) \end{aligned}$$

The above specification follows [27], which in turn cites [19]; refer to these sources for more detailed discussion of branch cuts, boundary conditions, and implementation of these functions. When it is possible these procedures produce a real result from a real argument.

(sqrt z)	procedure
----------	-----------

Returns the principal square root of z . The result will have either positive real part, or zero real part and nonnegative imaginary part.

(expt z_1 z_2) procedure

Returns z_1 raised to the power z_2 . For $z_1 \neq 0$

$$z_1^{z_2} = e^{z_2 \log z_1}$$

0^z is 1 if $z = 0$ and 0 otherwise.

(make-rectangular x_1 x_2) procedure

(make-polar x_3 x_4) procedure

(real-part z) procedure

(imag-part z) procedure

(magnitude z) procedure

(angle z) procedure

These procedures are part of every implementation that supports general complex numbers. Suppose x_1 , x_2 , x_3 , and x_4 are real numbers and z is a complex number such that

$$z = x_1 + x_2i = x_3 \cdot e^{ix_4}$$

Then

(make-rectangular x_1 x_2)	\implies	z
(make-polar x_3 x_4)	\implies	z
(real-part z)	\implies	x_1
(imag-part z)	\implies	x_2
(magnitude z)	\implies	$ x_3 $
(angle z)	\implies	x_{angle}

where $-\pi < x_{\text{angle}} \leq \pi$ with $x_{\text{angle}} = x_4 + 2\pi n$ for some integer n .

Rationale: Magnitude is the same as abs for a real argument, but abs must be present in all implementations, whereas magnitude need only be present in implementations that support general complex numbers.

(exact->inexact z) procedure

(inexact->exact z) procedure

Exact->inexact returns an inexact representation of z . The value returned is the inexact number that is numerically closest to the argument. If an exact argument has no reasonably close inexact equivalent, then a violation of an implementation restriction may be reported.

Inexact->exact returns an exact representation of z . The value returned is the exact number that is numerically closest to the argument. If an inexact argument has no reasonably close exact equivalent, then a violation of an implementation restriction may be reported.

These procedures implement the natural one-to-one correspondence between exact and inexact integers throughout an implementation-dependent range. See Section 7.2.3.

7.2.6. Numerical input and output.

```
(number->string z)                                procedure
(number->string z radix)                          procedure
```

Radix must be an exact integer, either 2, 8, 10, or 16. If omitted, *radix* defaults to 10. The procedure `number->string` takes a number and a radix and returns as a string an external representation of the given number in the given radix such that

```
(let ((number number)
      (radix radix))
  (eqv? number
        (string->number (number->string number
                        radix)
                        radix)))
```

is true. It is an error if no possible result makes this expression true.

If *z* is inexact, the radix is 10, and the above expression can be satisfied by a result that contains a decimal point, then the result contains a decimal point and is expressed using the minimum number of digits (exclusive of exponent and trailing zeroes) needed to make the above expression true [3, 5]; otherwise the format of the result is unspecified.

The result returned by `number->string` never contains an explicit radix prefix.

Note: The error case can occur only when *z* is not a complex number or is a complex number with a non-rational real or imaginary part.

Rationale: If *z* is an inexact number represented using flonums, and the radix is 10, then the above expression is normally satisfied by a result containing a decimal point. The unspecified case allows for infinities, NaNs, and nonflonum representations.

```
(string->number string)                          procedure
(string->number string radix)                    procedure
```

Returns a number of the maximally precise representation expressed by the given *string*. *Radix* must be an exact integer, either 2, 8, 10, or 16. If supplied, *radix* is a default radix that may be overridden by an explicit radix prefix in *string* (e.g., "#o177"). If *radix* is not supplied, then the default radix is 10. If *string* is not a syntactically valid notation for a number, then `string->number` returns #f.

```
(string->number "100")                            ⇒ 100
(string->number "100" 16)                         ⇒ 256
(string->number "1e2")                            ⇒ 100.0
(string->number "15##")                           ⇒ 1500.0
```

Note: The domain of `string->number` may be restricted by implementations in the following ways. `String->number` is permitted to return #f whenever *string* contains an explicit

radix prefix. If all numbers supported by an implementation are real, then `string->number` is permitted to return `#f` whenever *string* uses the polar or rectangular notations for complex numbers. If all numbers are integers, then `string->number` may return `#f` whenever the fractional notation is used. If all numbers are exact, then `string->number` may return `#f` whenever an exponent marker or explicit exactness prefix is used, or if a `#` appears in place of a digit. If all inexact numbers are integers, then `string->number` may return `#f` whenever a decimal point is used.

7.3. Other data types

This section describes operations on some of Scheme's non-numeric data types: booleans, pairs, lists, symbols, characters, strings and vectors.

7.3.1. Booleans. The standard boolean objects for true and false are written as `#t` and `#f`. What really matters, though, are the objects that the Scheme conditional expressions (`if`, `cond`, `and`, `or`, `do`) treat as true or false. The phrase "a true value" (or sometimes just "true") means any object treated as true by the conditional expressions, and the phrase "a false value" (or "false") means any object treated as false by the conditional expressions.

Of all the standard Scheme values, only `#f` counts as false in conditional expressions. Except for `#f`, all standard Scheme values, including `#t`, pairs, the empty list, symbols, numbers, strings, vectors, and procedures, count as true.

Note: Programmers accustomed to other dialects of Lisp should be aware that Scheme distinguishes both `#f` and the empty list from the symbol `nil`.

Boolean constants evaluate to themselves, so they do not need to be quoted in programs.

<code>#t</code>	\implies	<code>#t</code>
<code>#f</code>	\implies	<code>#f</code>
<code>'#f</code>	\implies	<code>#f</code>

`(not obj)`

library procedure

Not returns `#t` if *obj* is false, and returns `#f` otherwise.

<code>(not #t)</code>	\implies	<code>#f</code>
<code>(not 3)</code>	\implies	<code>#f</code>
<code>(not (list 3))</code>	\implies	<code>#f</code>
<code>(not #f)</code>	\implies	<code>#t</code>
<code>(not '())</code>	\implies	<code>#f</code>
<code>(not (list))</code>	\implies	<code>#f</code>
<code>(not 'nil)</code>	\implies	<code>#f</code>

`(boolean? obj)`

library procedure

Boolean? returns #t if *obj* is either #t or #f and returns #f otherwise.

(boolean? #f)	⇒	#t
(boolean? 0)	⇒	#f
(boolean? '())	⇒	#f

7.3.2. Pairs and lists. A *pair* (sometimes called a *dotted pair*) is a record structure with two fields called the *car* and *cdr* fields (for historical reasons). Pairs are created by the procedure *cons*. The *car* and *cdr* fields are accessed by the procedures *car* and *cdr*. The *car* and *cdr* fields are assigned by the procedures *set-car!* and *set-cdr!*.

Pairs are used primarily to represent lists. A list can be defined recursively as either the empty list or a pair whose *cdr* is a list. More precisely, the set of lists is defined as the smallest set *X* such that

- The empty list is in *X*.
- If *list* is in *X*, then any pair whose *cdr* field contains *list* is also in *X*.

The objects in the *car* fields of successive pairs of a list are the elements of the list. For example, a two-element list is a pair whose *car* is the first element and whose *cdr* is a pair whose *car* is the second element and whose *cdr* is the empty list. The length of a list is the number of elements, which is the same as the number of pairs.

The empty list is a special object of its own type (it is not a pair); it has no elements and its length is zero.

Note: The above definitions imply that all lists have finite length and are terminated by the empty list.

The most general notation (external representation) for Scheme pairs is the “dotted” notation $(c_1 . c_2)$ where c_1 is the value of the *car* field and c_2 is the value of the *cdr* field. For example $(4 . 5)$ is a pair whose *car* is 4 and whose *cdr* is 5. Note that $(4 . 5)$ is the external representation of a pair, not an expression that evaluates to a pair.

A more streamlined notation can be used for lists: the elements of the list are simply enclosed in parentheses and separated by spaces. The empty list is written $()$. For example,

(a b c d e)

and

(a . (b . (c . (d . (e . ())))))

are equivalent notations for a list of symbols.

A chain of pairs not ending in the empty list is called an *improper list*. Note that an improper list is not a list. The list and dotted notations can be combined to represent improper lists:

(a b c . d)

is equivalent to

```
(a . (b . (c . d)))
```

Whether a given pair is a list depends upon what is stored in the `cdr` field. When the `set-cdr!` procedure is used, an object can be a list one moment and not the next:

```
(define x (list 'a 'b 'c))
(define y x)
y                                     ⇒ (a b c)
(list? y)                             ⇒ #t
(set-cdr! x 4)                         ⇒ unspecified
x                                       ⇒ (a . 4)
(eqv? x y)                             ⇒ #t
y                                       ⇒ (a . 4)
(list? y)                             ⇒ #f
(set-cdr! x x)                         ⇒ unspecified
(list? x)                               ⇒ #f
```

Within literal expressions and representations of objects read by the `read` procedure, the forms `'(datum)`, ``(datum)`, `,(datum)`, and `,@(datum)` denote two-element lists whose first elements are the symbols `quote`, `quasiquote`, `unquote`, and `unquote-splicing`, respectively. The second element in each case is `(datum)`. This convention is supported so that arbitrary Scheme programs may be represented as lists. That is, according to Scheme's grammar, every `(expression)` is also a `(datum)` (see Section 8.1.2). Among other things, this permits the use of the `read` procedure to parse Scheme programs. See Section 4.3.

`(pair? obj)` procedure

Pair? returns `#t` if `obj` is a pair, and otherwise returns `#f`.

```
(pair? '(a . b))                       ⇒ #t
(pair? '(a b c))                       ⇒ #t
(pair? '())                             ⇒ #f
(pair? '#(a b))                         ⇒ #f
```

`(cons obj1 obj2)` procedure

Returns a newly allocated pair whose `car` is `obj1` and whose `cdr` is `obj2`. The pair is guaranteed to be different (in the sense of `eqv?`) from every existing object.

```
(cons 'a '())                           ⇒ (a)
(cons '(a) '(b c d))                    ⇒ ((a) b c d)
(cons "a" '(b c))                       ⇒ ("a" b c)
(cons 'a 3)                              ⇒ (a . 3)
(cons '(a b) 'c)                        ⇒ ((a b) . c)
```

`(car pair)` procedure

Returns the contents of the car field of *pair*. Note that it is an error to take the car of the empty list.

```
(car '(a b c))           ⇒ a
(car '((a) b c d))      ⇒ (a)
(car '(1 . 2))          ⇒ 1
(car '())                ⇒ error
```

(cdr *pair*) procedure

Returns the contents of the cdr field of *pair*. Note that it is an error to take the cdr of the empty list.

```
(cdr '((a) b c d))      ⇒ (b c d)
(cdr '(1 . 2))          ⇒ 2
(cdr '())                ⇒ error
```

(set-car! *pair obj*) procedure

Stores *obj* in the car field of *pair*. The value returned by `set-car!` is unspecified.

```
(define (f) (list 'not-a-constant-list))
(define (g) '(constant-list))
(set-car! (f) 3)          ⇒ unspecified
(set-car! (g) 3)          ⇒ error
```

(set-cdr! *pair obj*) procedure

Stores *obj* in the cdr field of *pair*. The value returned by `set-cdr!` is unspecified.

(caar <i>pair</i>)	library procedure
(cadr <i>pair</i>)	library procedure
⋮	⋮
(caddr <i>pair</i>)	library procedure
(caddr <i>pair</i>)	library procedure

These procedures are compositions of `car` and `cdr`, where for example `caddr` could be defined by

```
(define caddr (lambda (x) (car (cdr (cdr x))))).
```

Arbitrary compositions, up to four deep, are provided. There are twenty-eight of these procedures in all.

`(null? obj)` library procedure

Returns `#t` if *obj* is the empty list, otherwise returns `#f`.

`(list? obj)` library procedure

Returns `#t` if *obj* is a list, otherwise returns `#f`. By definition, all lists have finite length and are terminated by the empty list.

```
(list? '(a b c))      => #t
(list? '())           => #t
(list? '(a . b))      => #f
(let ((x (list 'a)))
  (set-cdr! x x)
  (list? x))          => #f
```

`(list obj ...)` library procedure

Returns a newly allocated list of its arguments.

```
(list 'a (+ 3 4) 'c)  => (a 7 c)
(list)                => ()
```

`(length list)` library procedure

Returns the length of *list*.

```
(length '(a b c))      => 3
(length '(a (b) (c d e))) => 3
(length '())           => 0
```

`(append list ...)` library procedure

Returns a list consisting of the elements of the first *list* followed by the elements of the other *lists*.

```
(append '(x) '(y))      => (x y)
(append '(a) '(b c d)) => (a b c d)
(append '(a (b)) '((c))) => (a (b) (c))
```

The resulting list is always newly allocated, except that it shares structure with the last *list* argument. The last argument may actually be any object; an improper list results if the last argument is not a proper list.

```
(append '(a b) '(c . d))    ⇒ (a b c . d)
(append '() 'a)             ⇒ a
```

(reverse *list*) library procedure

Returns a newly allocated list consisting of the elements of *list* in reverse order.

```
(reverse '(a b c))          ⇒ (c b a)
(reverse '(a (b c) d (e (f)))) ⇒ ((e (f)) d (b c) a)
```

(list-tail *list* *k*) library procedure

Returns the sublist of *list* obtained by omitting the first *k* elements. It is an error if *list* has fewer than *k* elements. List-tail could be defined by

```
(define list-tail
  (lambda (x k)
    (if (zero? k)
        x
        (list-tail (cdr x) (- k 1)))))
```

(list-ref *list* *k*) library procedure

Returns the *k*th element of *list*. (This is the same as the car of (list-tail *list* *k*.) It is an error if *list* has fewer than *k* elements.

```
(list-ref '(a b c d) 2)    ⇒ c
(list-ref '(a b c d)
  (inexact->exact (round 1.8))) ⇒ c
```

(memq *obj list*) library procedure

(memv *obj list*) library procedure

(member *obj list*) library procedure

These procedures return the first sublist of *list* whose car is *obj*, where the sublists of *list* are the non-empty lists returned by (list-tail *list* *k*) for *k* less than the length of *list*. If *obj* does not occur in *list*, then #f (not the empty list) is returned. Memq uses eq? to compare *obj* with the elements of *list*, while memv uses eqv? and member uses equal?.

```
(memq 'a '(a b c))    ⇒ (a b c)
(memq 'b '(a b c))    ⇒ (b c)
(memq 'a '(b c d))    ⇒ #f
```

```

(memq (list 'a) '(b (a) c))      ⇒ #f
(member (list 'a)
        '(b (a) c))             ⇒ ((a) c)
(memq 101 '(100 101 102))       ⇒ unspecified
(memv 101 '(100 101 102))       ⇒ (101 102)

```

```

(assq obj alist)                library procedure
(assv obj alist)                library procedure
(assoc obj alist)               library procedure

```

Alist (for “association list”) must be a list of pairs. These procedures find the first pair in *alist* whose car field is *obj*, and returns that pair. If no pair in *alist* has *obj* as its car, then *#f* (not the empty list) is returned. *Assq* uses *eq?* to compare *obj* with the car fields of the pairs in *alist*, while *assv* uses *eqv?* and *assoc* uses *equal?*.

```

(define e '((a 1)(b 2)(c 3)))
(assq 'a e)                      ⇒ (a 1)
(assq 'b e)                      ⇒ (b 2)
(assq 'd e)                      ⇒ #f
(assq (list 'a) '((a)) ((b)) ((c))))
                                  ⇒ #f
(assoc (list 'a) '((a)) ((b)) ((c))))
                                  ⇒ ((a))
(assq 5 '((2 3) (5 7) (11 13)))   ⇒ unspecified
(assv 5 '((2 3) (5 7) (11 13)))   ⇒ (5 7)

```

Rationale: Although they are ordinarily used as predicates, *memq*, *memv*, *member*, *assq*, *assv*, and *assoc* do not have question marks in their names because they return useful values rather than just *#t* or *#f*.

7.3.3. Symbols. Symbols are objects whose usefulness rests on the fact that two symbols are identical (in the sense of *eqv?*) if and only if their names are spelled the same way. This is exactly the property needed to represent identifiers in programs, and so most implementations of Scheme use them internally for that purpose. Symbols are useful for many other applications; for instance, they may be used the way enumerated values are used in Pascal.

The rules for writing a symbol are exactly the same as the rules for writing an identifier; see Sections 3.1 and 8.1.1.

It is guaranteed that any symbol that has been returned as part of a literal expression, or read using the *read* procedure, and subsequently written out using the *write* procedure, will read back in as the identical symbol (in the sense of *eqv?*). The *string->symbol* procedure, however, can create symbols for which this write/read invariance may not hold because their names contain special characters or letters in the nonstandard case.

Note: Some implementations of Scheme have a feature known as “slashification” in order to guarantee write/read invariance for all symbols, but historically the most important use of this feature has been to compensate for the lack of a string data type.

Some implementations also have “uninterned symbols”, which defeat write/read invariance even in implementations with slashification, and also generate exceptions to the rule that two symbols are the same if and only if their names are spelled the same.

(symbol? *obj*) procedure

Returns #t if *obj* is a symbol, otherwise returns #f.

```
(symbol? 'foo)           ⇒ #t
(symbol? (car '(a b)))  ⇒ #t
(symbol? "bar")         ⇒ #f
(symbol? 'nil)          ⇒ #t
(symbol? '())           ⇒ #f
(symbol? #f)            ⇒ #f
```

(symbol->string *symbol*) procedure

Returns the name of *symbol* as a string. If the symbol was part of an object returned as the value of a literal expression (Section 5.1.2) or by a call to the read procedure, and its name contains alphabetic characters, then the string returned will contain characters in the implementation’s preferred standard case—some implementations will prefer upper case, others lower case. If the symbol was returned by string->symbol, the case of characters in the string returned will be the same as the case in the string that was passed to string->symbol. It is an error to apply mutation procedures like string-set! to strings returned by this procedure.

The following examples assume that the implementation’s standard case is lower case:

```
(symbol->string 'flying-fish) ⇒ "flying-fish"
(symbol->string 'Martin)     ⇒ "martin"
(symbol->string
  (string->symbol "Malvina")) ⇒ "Malvina"
```

(string->symbol *string*) procedure

Returns the symbol whose name is *string*. This procedure can create symbols with names containing special characters or letters in the nonstandard case, but it is usually a bad idea to create such symbols because in some implementations of Scheme they cannot be read as themselves. See symbol->string.

The following examples assume that the implementation’s standard case is lower case:

```
(eq? 'mISSISSIppi 'mississippi) ⇒ #t
(string->symbol "mISSISSIppi")   ⇒ the symbol with name
                                   "mISSISSIppi"
```

```

(eq? 'bitBlt (string->symbol "bitBlt"))
                                     ⇒ #f
(eq? 'JollyWog
  (string->symbol
    (symbol->string 'JollyWog)))
                                     ⇒ #t
(string=? "K. Harper, M.D."
  (symbol->string
    (string->symbol "K. Harper, M.D.")))
                                     ⇒ #t

```

7.3.4. Characters. Characters are objects that represent printed characters such as letters and digits. Characters are written using the notation `#\⟨character⟩` or `#\⟨character name⟩`. For example:

```

#\a      ; lower case letter
#\A      ; upper case letter
#\ (     ; left parenthesis
#\       ; the space character
#\space  ; the preferred way to write a space
#\newline ; the newline character

```

Case is significant in `#\⟨character⟩`, but not in `#\⟨character name⟩`. If `⟨character⟩` in `#\⟨character⟩` is alphabetic, then the character following `⟨character⟩` must be a delimiter character such as a space or parenthesis. This rule resolves the ambiguous case where, for example, the sequence of characters “`#\space`” could be taken to be either a representation of the space character or a representation of the character “`#\s`” followed by a representation of the symbol “`pace`.”

Characters written in the `#\` notation are self-evaluating. That is, they do not have to be quoted in programs.

Some of the procedures that operate on characters ignore the difference between upper case and lower case. The procedures that ignore case have “`-ci`” (for “case insensitive”) embedded in their names.

`(char? obj)` procedure

Returns `#t` if `obj` is a character, otherwise returns `#f`.

<code>(char=? char₁ char₂)</code>	procedure
<code>(char<? char₁ char₂)</code>	procedure
<code>(char>? char₁ char₂)</code>	procedure
<code>(char<=? char₁ char₂)</code>	procedure
<code>(char>=? char₁ char₂)</code>	procedure

These procedures impose a total ordering on the set of characters. It is guaranteed that under this ordering:

- The upper case characters are in order. For example, $(\text{char}<? \#\backslash\text{A} \#\backslash\text{B})$ returns $\#t$.
- The lower case characters are in order. For example, $(\text{char}<? \#\backslash\text{a} \#\backslash\text{b})$ returns $\#t$.
- The digits are in order. For example, $(\text{char}<? \#\backslash\text{0} \#\backslash\text{9})$ returns $\#t$.
- Either all the digits precede all the upper case letters, or vice versa.
- Either all the digits precede all the lower case letters, or vice versa.

Some implementations may generalize these procedures to take more than two arguments, as with the corresponding numerical predicates.

$(\text{char-ci}=? \text{char}_1 \text{char}_2)$	library procedure
$(\text{char-ci}<? \text{char}_1 \text{char}_2)$	library procedure
$(\text{char-ci}>? \text{char}_1 \text{char}_2)$	library procedure
$(\text{char-ci}<=? \text{char}_1 \text{char}_2)$	library procedure
$(\text{char-ci}>=? \text{char}_1 \text{char}_2)$	library procedure

These procedures are similar to $\text{char}=?$ et cetera, but they treat upper case and lower case letters as the same. For example, $(\text{char-ci}=? \#\backslash\text{A} \#\backslash\text{a})$ returns $\#t$. Some implementations may generalize these procedures to take more than two arguments, as with the corresponding numerical predicates.

$(\text{char-alphabetic}? \text{char})$	library procedure
$(\text{char-numeric}? \text{char})$	library procedure
$(\text{char-whitespace}? \text{char})$	library procedure
$(\text{char-upper-case}? \text{letter})$	library procedure
$(\text{char-lower-case}? \text{letter})$	library procedure

These procedures return $\#t$ if their arguments are alphabetic, numeric, whitespace, upper case, or lower case characters, respectively, otherwise they return $\#f$. The following remarks, which are specific to the ASCII character set, are intended only as a guide: The alphabetic characters are the 52 upper and lower case letters. The numeric characters are the ten decimal digits. The whitespace characters are space, tab, line feed, form feed, and carriage return.

$(\text{char}\rightarrow\text{integer} \text{char})$	procedure
$(\text{integer}\rightarrow\text{char} n)$	procedure

Given a character, $\text{char}\rightarrow\text{integer}$ returns an exact integer representation of the character. Given an exact integer that is the image of a character under $\text{char}\rightarrow\text{integer}$, $\text{integer}\rightarrow\text{char}$ returns that character. These procedures implement order-preserving isomorphisms between the set of characters under the $\text{char}<=?$ ordering and some subset of the integers under the $<=?$ ordering. That is, if

$$(\text{char}<=? a b \implies \#t \text{ and } (<=? x y) \implies \#t$$

and x and y are in the domain of $\text{integer}\rightarrow\text{char}$, then

```
(<= (char->integer a)
     (char->integer b))           => #t
```

```
(char<=? (integer->char x)
         (integer->char y))       => #t
```

```
(char-upcase char)               library procedure
(char-downcase char)             library procedure
```

These procedures return a character $char_2$ such that $(char-ci=? char char_2)$. In addition, if $char$ is alphabetic, then the result of `char-upcase` is upper case and the result of `char-downcase` is lower case.

7.3.5. Strings. Strings are sequences of characters. Strings are written as sequences of characters enclosed within doublequotes ("). A doublequote can be written inside a string only by escaping it with a backslash (\), as in

```
"The word \"recursion\" has many meanings."
```

A backslash can be written inside a string only by escaping it with another backslash. Scheme does not specify the effect of a backslash within a string that is not followed by a doublequote or backslash.

A string constant may continue from one line to the next, but the exact contents of such a string are unspecified.

The *length* of a string is the number of characters that it contains. This number is an exact, non-negative integer that is fixed when the string is created. The *valid indexes* of a string are the exact nonnegative integers less than the length of the string. The first character of a string has index 0, the second has index 1, and so on.

In phrases such as “the characters of *string* beginning with index *start* and ending with index *end*,” it is understood that the index *start* is inclusive and the index *end* is exclusive. Thus if *start* and *end* are the same index, a null substring is referred to, and if *start* is zero and *end* is the length of *string*, then the entire string is referred to.

Some of the procedures that operate on strings ignore the difference between upper and lower case. The versions that ignore case have “-ci” (for “case insensitive”) embedded in their names.

```
(string? obj)                     procedure
```

Returns #t if *obj* is a string, otherwise returns #f.

```
(make-string k)                   procedure
(make-string k char)              procedure
```

`Make-string` returns a newly allocated string of length k . If $char$ is given, then all elements of the string are initialized to $char$, otherwise the contents of the *string* are unspecified.

`(string char ...)` library procedure

Returns a newly allocated string composed of the arguments.

`(string-length string)` procedure

Returns the number of characters in the given *string*.

`(string-ref string k)` procedure

k must be a valid index of *string*. `String-ref` returns character *k* of *string* using zero-origin indexing.

`(string-set! string k char)` procedure

k must be a valid index of *string*. `String-set!` stores *char* in element *k* of *string* and returns an unspecified value.

```
(define (f) (make-string 3 #\*))
(define (g) "***")
(string-set! (f) 0 #\?)           ⇒ unspecified
(string-set! (g) 0 #\?)           ⇒ error
(string-set! (symbol->string 'immutable)
             0
             #\?)                 ⇒ error
```

`(string=? string1 string2)` library procedure

`(string-ci=? string1 string2)` library procedure

Returns `#t` if the two strings are the same length and contain the same characters in the same positions, otherwise returns `#f`. `String-ci=?` treats upper and lower case letters as though they were the same character, but `string=?` treats upper and lower case as distinct characters.

`(string<? string1 string2)` library procedure

`(string>? string1 string2)` library procedure

`(string<=? string1 string2)` library procedure

`(string>=? string1 string2)` library procedure

`(string-ci<? string1 string2)` library procedure

`(string-ci>? string1 string2)` library procedure

`(string-ci<=? string1 string2)` library procedure

`(string-ci>=? string1 string2)` library procedure

These procedures are the lexicographic extensions to strings of the corresponding orderings on characters. For example, `string<?` is the lexicographic ordering on strings induced

by the ordering `char<?` on characters. If two strings differ in length but are the same up to the length of the shorter string, the shorter string is considered to be lexicographically less than the longer string.

Implementations may generalize these and the `string=?` and `string-ci=?` procedures to take more than two arguments, as with the corresponding numerical predicates.

`(substring string start end)` library procedure

String must be a string, and *start* and *end* must be exact integers satisfying

$$0 \leq \textit{start} \leq \textit{end} \leq (\textit{string-length string}).$$

`substring` returns a newly allocated string formed from the characters of *string* beginning with index *start* (inclusive) and ending with index *end* (exclusive).

`(string-append string ...)` library procedure

Returns a newly allocated string whose characters form the concatenation of the given strings.

`(string->list string)` library procedure
`(list->string list)` library procedure

`String->list` returns a newly allocated list of the characters that make up the given string. `List->string` returns a newly allocated string formed from the characters in the list *list*, which must be a list of characters. `String->list` and `list->string` are inverses so far as `equal?` is concerned.

`(string-copy string)` library procedure

Returns a newly allocated copy of the given *string*.

`(string-fill! string char)` library procedure

Stores *char* in every element of the given *string* and returns an unspecified value.

7.3.6. Vectors. Vectors are heterogenous structures whose elements are indexed by integers. A vector typically occupies less space than a list of the same length, and the average time required to access a randomly chosen element is typically less for the vector than for the list.

The *length* of a vector is the number of elements that it contains. This number is a nonnegative integer that is fixed when the vector is created. The *valid indexes* of a vector are the exact nonnegative integers less than the length of the vector. The first element in a vector is indexed by zero, and the last element is indexed by one less than the length of the vector.

Vectors are written using the notation `#(obj ...)`. For example, a vector of length 3 containing the number zero in element 0, the list `(2 2 2 2)` in element 1, and the string "Anna" in element 2 can be written as following:

```
#(0 (2 2 2 2) "Anna")
```

Note that this is the external representation of a vector, not an expression evaluating to a vector. Like list constants, vector constants must be quoted:

```
'#(0 (2 2 2 2) "Anna")           ⇒ #(0 (2 2 2 2) "Anna")
```

```
(vector? obj)
```

procedure

Returns `#t` if *obj* is a vector, otherwise returns `#f`.

```
(make-vector k)
```

procedure

```
(make-vector k fill)
```

procedure

Returns a newly allocated vector of *k* elements. If a second argument is given, then each element is initialized to *fill*. Otherwise the initial contents of each element is unspecified.

```
(vector obj ...)
```

library procedure

Returns a newly allocated vector whose elements contain the given arguments. Analogous to `list`.

```
(vector 'a 'b 'c)                 ⇒ #(a b c)
```

```
(vector-length vector)
```

procedure

Returns the number of elements in *vector* as an exact integer.

```
(vector-ref vector k)
```

procedure

k must be a valid index of *vector*. `Vector-ref` returns the contents of element *k* of *vector*.

```
(vector-ref '#(1 1 2 3 5 8 13 21)
            5)                ⇒ 8
```

```
(vector-ref '#(1 1 2 3 5 8 13 21)
            (let ((i (round (* 2 (acos -1))))))
              (if (inexact? i)
                  (inexact->exact i)
                  i)))        ⇒ 13
```

`(vector-set! vector k obj)` procedure

k must be a valid index of *vector*. `vector-set!` stores *obj* in element *k* of *vector*. The value returned by `vector-set!` is unspecified.

```
(let ((vec (vector 0 '(2 2 2) "Anna")))
  (vector-set! vec 1 '("Sue" "Sue")))
vec)                               ⇒ #(0 ("Sue" "Sue") "Anna")

(vector-set! '#(0 1 2) 1 "doe")    ⇒ error ; constant vector
```

`(vector->list vector)` library procedure
`(list->vector list)` library procedure

`vector->list` returns a newly allocated list of the objects contained in the elements of *vector*. `list->vector` returns a newly created vector initialized to the elements of the list *list*.

```
(vector->list '(dah dah didah))    ⇒ (dah dah didah)
(list->vector '(dididit dah))      ⇒ #(dididit dah)
```

`(vector-fill! vector fill)` library procedure

Stores *fill* in every element of *vector*. The value returned by `vector-fill!` is unspecified.

7.4. Control features

This section describes various primitive procedures which control the flow of program execution in special ways. The `procedure?` predicate is also described here.

`(procedure? obj)` procedure

Returns `#t` if *obj* is a procedure, otherwise returns `#f`.

```
(procedure? car)                    ⇒ #t
(procedure? 'car)                   ⇒ #f
(procedure? (lambda (x) (* x x)))  ⇒ #t
(procedure? '(lambda (x) (* x x))) ⇒ #f
(call-with-current-continuation procedure?) ⇒ #t
```

`(apply proc arg1 ... args)` procedure

Proc must be a procedure and *args* must be a list. Calls *proc* with the elements of the list `(append (list arg1 ...) args)` as the actual arguments.

`(apply + (list 3 4))` ⇒ 7

```
(define compose
  (lambda (f g)
    (lambda args
      (f (apply g args))))))
```

`((compose sqrt *) 12 75)` ⇒ 30

`(map proc list1 list2 ...)` library procedure

The *lists* must be lists, and *proc* must be a procedure taking as many arguments as there are *lists* and returning a single value. If more than one *list* is given, then they must all be the same length. `map` applies *proc* element-wise to the elements of the *lists* and returns a list of the results, in order. The dynamic order in which *proc* is applied to the elements of the *lists* is unspecified.

`(map cadr '((a b) (d e) (g h)))` ⇒ (b e h)

`(map (lambda (n) (expt n n))
'(1 2 3 4 5))` ⇒ (1 4 27 256 3125)

`(map + '(1 2 3) '(4 5 6))` ⇒ (5 7 9)

```
(let ((count 0))
  (map (lambda (ignored)
        (set! count (+ count 1))
        count)
    '(a b)))
```

⇒ (1 2) or (2 1)

`(for-each proc list1 list2 ...)` library procedure

The arguments to `for-each` are like the arguments to `map`, but `for-each` calls *proc* for its side effects rather than for its values. Unlike `map`, `for-each` is guaranteed to call *proc* on the elements of the *lists* in order from the first element(s) to the last, and the value returned by `for-each` is unspecified.

```
(let ((v (make-vector 5)))
  (for-each (lambda (i)
```


Here is a possible implementation of `delay` and `force`. Promises are implemented here as procedures of no arguments, and `force` simply calls its argument:

```
(define force
  (lambda (object)
    (object)))
```

We define the expression

```
(delay (expression))
```

to have the same meaning as the procedure call

```
(make-promise (lambda () (expression)))
```

as follows

```
(define-syntax delay
  (syntax-rules ()
    ((delay expression)
     (make-promise (lambda () expression))))),
```

where `make-promise` is defined as follows:

```
(define make-promise
  (lambda (proc)
    (let ((result-ready? #f)
          (result #f))
      (lambda ()
        (if result-ready?
            result
            (let ((x (proc)))
              (if result-ready?
                  result
                  (begin (set! result-ready? #t)
                         (set! result x)
                         result))))))))))
```

Rationale: A promise may refer to its own value, as in the last example above. Forcing such a promise may cause the promise to be forced a second time before the value of the first force has been computed. This complicates the definition of `make-promise`.

Various extensions to this semantics of `delay` and `force` are supported in some implementations:

- Calling `force` on an object that is not a promise may simply return the object.

- It may be the case that there is no means by which a promise can be operationally distinguished from its forced value. That is, expressions like the following may evaluate to either `#t` or to `#f`, depending on the implementation:

```
(equiv? (delay 1) 1)           ⇒ unspecified
(pair? (delay (cons 1 2)))     ⇒ unspecified
```

- Some implementations may implement “implicit forcing,” where the value of a promise is forced by primitive procedures like `cdr` and `+`:

```
(+ (delay (* 3 7)) 13)         ⇒ 34
```

```
(call-with-current-continuation proc)           procedure
```

Proc must be a procedure of one argument. The procedure `call-with-current-continuation` packages up the current continuation (see the rationale below) as an “escape procedure” and passes it as an argument to *proc*. The escape procedure is a Scheme procedure that, if it is later called, will abandon whatever continuation is in effect at that later time and will instead use the continuation that was in effect when the escape procedure was created. Calling the escape procedure may cause the invocation of *before* and *after* thunks installed using `dynamic-wind`.

The escape procedure accepts the same number of arguments as the continuation to the original call to `call-with-current-continuation`. Except for continuations created by the `call-with-values` procedure, all continuations take exactly one value. The effect of passing no value or more than one value to continuations that were not created by `call-with-values` is unspecified.

The escape procedure that is passed to *proc* has unlimited extent just like any other procedure in Scheme. It may be stored in variables or data structures and may be called as many times as desired.

The following examples show only the most common ways in which `call-with-current-continuation` is used. If all real uses were as simple as these examples, there would be no need for a procedure with the power of `call-with-current-continuation`.

```
(call-with-current-continuation
 (lambda (exit)
  (for-each (lambda (x)
             (if (negative? x)
                 (exit x)))
           '(54 0 37 -3 245 19))
  #t)) ⇒ -3
```

```
(define list-length
```

```

(lambda (obj)
  (call-with-current-continuation
    (lambda (return)
      (letrec ((r
                 (lambda (obj)
                   (cond ((null? obj) 0)
                         ((pair? obj)
                          (+ (r (cdr obj)) 1))
                         (else (return #f))))))
        (r obj))))))

(list-length '(1 2 3 4))           ⇒ 4

(list-length '(a b . c))          ⇒ #f

```

Rationale: A common use of `call-with-current-continuation` is for structured, non-local exits from loops or procedure bodies, but in fact `call-with-current-continuation` is extremely useful for implementing a wide variety of advanced control structures.

Whenever a Scheme expression is evaluated there is a *continuation* wanting the result of the expression. The continuation represents an entire (default) future for the computation. If the expression is evaluated at top level, for example, then the continuation might take the result, print it on the screen, prompt for the next input, evaluate it, and so on forever. Most of the time the continuation includes actions specified by user code, as in a continuation that will take the result, multiply it by the value stored in a local variable, add seven, and give the answer to the top level continuation to be printed. Normally these ubiquitous continuations are hidden behind the scenes and programmers do not think much about them. On rare occasions, however, a programmer may need to deal with continuations explicitly. `Call-with-current-continuation` allows Scheme programmers to do that by creating a procedure that acts just like the current continuation.

Most programming languages incorporate one or more special-purpose escape constructs with names like `exit`, `return`, or even `goto`. In 1965, however, Peter Landin [16] invented a general purpose escape operator called the J-operator. John Reynolds [24] described a simpler but equally powerful construct in 1972. The `catch` special form described by Sussman and Steele in the 1975 report on Scheme is exactly the same as Reynolds's construct, though its name came from a less general construct in MacLisp. Several Scheme implementors noticed that the full power of the `catch` construct could be provided by a procedure instead of by a special syntactic construct, and the name `call-with-current-continuation` was coined in 1982. This name is descriptive, but opinions differ on the merits of such a long name, and some people use the name `call/cc` instead.

(values *obj* ...) procedure

Delivers all of its arguments to its continuation. Except for continuations created by the `call-with-values` procedure, all continuations take exactly one value.

Values might be defined as follows:

```
(define (values . things)
  (call-with-current-continuation
    (lambda (cont) (apply cont things))))
```

(call-with-values *producer consumer*) procedure

Calls its *producer* argument with no values and a continuation that, when passed some values, calls the *consumer* procedure with those values as arguments. The continuation for the call to *consumer* is the continuation of the call to call-with-values.

```
(call-with-values (lambda () (values 4 5))
  (lambda (a b) b))
      ⇒ 5
```

```
(call-with-values * -)      ⇒ -1
```

(dynamic-wind *before thunk after*) procedure

Calls *thunk* without arguments, returning the result(s) of this call. *Before* and *after* are called, also without arguments, as required by the following rules (note that in the absence of calls to continuations captured using call-with-current-continuation the three arguments are called once each, in order). *Before* is called whenever execution enters the dynamic extent of the call to *thunk* and *after* is called whenever it exits that dynamic extent. The dynamic extent of a procedure call is the period between when the call is initiated and when it returns. In Scheme, because of call-with-current-continuation, the dynamic extent of a call may not be a single, connected time period. It is defined as follows:

- The dynamic extent is entered when execution of the body of the called procedure begins.
- The dynamic extent is also entered when execution is not within the dynamic extent and a continuation is invoked that was captured (using call-with-current-continuation) during the dynamic extent.
- It is exited when the called procedure returns.
- It is also exited when execution is within the dynamic extent and a continuation is invoked that was captured while not within the dynamic extent.

If a second call to dynamic-wind occurs within the dynamic extent of the call to *thunk* and then a continuation is invoked in such a way that the *afters* from these two invocations of dynamic-wind are both to be called, then the *after* associated with the second (inner) call to dynamic-wind is called first.

If a second call to dynamic-wind occurs within the dynamic extent of the call to *thunk* and then a continuation is invoked in such a way that the *befores* from these two invocations

of `dynamic-wind` are both to be called, then the *before* associated with the first (outer) call to `dynamic-wind` is called first.

If invoking a continuation requires calling the *before* from one call to `dynamic-wind` and the *after* from another, then the *after* is called first.

The effect of using a captured continuation to enter or exit the dynamic extent of a call to *before* or *after* is undefined.

```
(let ((path '())
      (c #f))
  (let ((add (lambda (s)
               (set! path (cons s path))))))
    (dynamic-wind
      (lambda () (add 'connect))
      (lambda ()
        (add (call-with-current-continuation
              (lambda (c0)
                (set! c c0)
                'talk1))))))
      (lambda () (add 'disconnect)))
    (if (< (length path) 4)
        (c 'talk2)
        (reverse path))))          => (connect talk1 disconnect
                                       connect talk2 disconnect)
```

7.5. Eval

(eval *expression environment-specifier*) procedure

Evaluates *expression* in the specified environment and returns its value. *Expression* must be a valid Scheme expression represented as data, and *environment-specifier* must be a value returned by one of the three procedures described below. Implementations may extend `eval` to allow nonexpression programs (definitions) as the first argument and to allow other values as environments, with the restriction that `eval` is not allowed to create new bindings in the environments associated with `null-environment` or `scheme-report-environment`.

```
(eval '(* 7 3) (scheme-report-environment 5))
                                     => 21
(let ((f (eval '(lambda (f x) (f x x))
               (null-environment 5))))
  (f + 10))                          => 20
```

(scheme-report-environment *version*) procedure
 (null-environment *version*) procedure

Version must be the exact integer 5, corresponding to this revision of the Scheme report (the Revised⁵ Report on Scheme). `scheme-report-environment` returns a specifier for an environment that is empty except for all bindings defined in this report that are either required or both optional and supported by the implementation. `Null-environment` returns a specifier for an environment that is empty except for the (syntactic) bindings for all syntactic keywords defined in this report that are either required or both optional and supported by the implementation.

Other values of *version* can be used to specify environments matching past revisions of this report, but their support is not required. An implementation will signal an error if *version* is neither 5 nor another value supported by the implementation.

The effect of assigning (through the use of `eval`) a variable bound in a `scheme-report-environment` (for example `car`) is unspecified. Thus the environments specified by `scheme-report-environment` may be immutable.

`(interaction-environment)` optional procedure

This procedure returns a specifier for the environment that contains implementation-defined bindings, typically a superset of those listed in the report. The intent is that this procedure will return the environment in which the implementation would evaluate expressions dynamically typed by the user.

7.6. *Input and output*

7.6.1. Ports. Ports represent input and output devices. To Scheme, an input port is a Scheme object that can deliver characters upon command, while an output port is a Scheme object that can accept characters.

`(call-with-input-file string proc)` library procedure
`(call-with-output-file string proc)` library procedure

String should be a string naming a file, and *proc* should be a procedure that accepts one argument. For `call-with-input-file`, the file should already exist; for `call-with-output-file`, the effect is unspecified if the file already exists. These procedures call *proc* with one argument: the port obtained by opening the named file for input or output. If the file cannot be opened, an error is signalled. If *proc* returns, then the port is closed automatically and the value(s) yielded by the *proc* is(are) returned. If *proc* does not return, then the port will not be closed automatically unless it is possible to prove that the port will never again be used for a read or write operation.

Rationale: Because Scheme's escape procedures have unlimited extent, it is possible to escape from the current continuation but later to escape back in. If implementations were permitted to close the port on any escape from the current continuation, then it would be impossible to write portable code using both `call-with-current-continuation` and `call-with-input-file` or `call-with-output-file`.

(input-port? *obj*) procedure
 (output-port? *obj*) procedure

Returns #t if *obj* is an input port or output port respectively, otherwise returns #f.

(current-input-port) procedure
 (current-output-port) procedure

Returns the current default input or output port.

(with-input-from-file *string thunk*) optional procedure
 (with-output-to-file *string thunk*) optional procedure

String should be a string naming a file, and *proc* should be a procedure of no arguments. For *with-input-from-file*, the file should already exist; for *with-output-to-file*, the effect is unspecified if the file already exists. The file is opened for input or output, an input or output port connected to it is made the default value returned by *current-input-port* or *current-output-port* (and is used by *(read)*, *(write obj)*, and so forth), and the *thunk* is called with no arguments. When the *thunk* returns, the port is closed and the previous default is restored. *With-input-from-file* and *with-output-to-file* return(s) the value(s) yielded by *thunk*. If an escape procedure is used to escape from the continuation of these procedures, their behavior is implementation dependent.

(open-input-file *filename*) procedure

Takes a string naming an existing file and returns an input port capable of delivering characters from the file. If the file cannot be opened, an error is signalled.

(open-output-file *filename*) procedure

Takes a string naming an output file to be created and returns an output port capable of writing characters to a new file by that name. If the file cannot be opened, an error is signalled. If a file with the given name already exists, the effect is unspecified.

(close-input-port *port*) procedure
 (close-output-port *port*) procedure

Closes the file associated with *port*, rendering the *port* incapable of delivering or accepting characters. These routines have no effect if the file has already been closed. The value returned is unspecified.

7.6.2. *Input.*

(read)	library procedure
(read <i>port</i>)	library procedure

Read converts external representations of Scheme objects into the objects themselves. That is, it is a parser for the nonterminal `<datum>` (see Sections 8.1.2 and 7.3.2). Read returns the next object parsable from the given input *port*, updating *port* to point to the first character past the end of the external representation of the object.

If an end of file is encountered in the input before any characters are found that can begin an object, then an end of file object is returned. The port remains open, and further attempts to read will also return an end of file object. If an end of file is encountered after the beginning of an object's external representation, but the external representation is incomplete and therefore not parsable, an error is signalled.

The *port* argument may be omitted, in which case it defaults to the value returned by `current-input-port`. It is an error to read from a closed port.

(read-char)	procedure
(read-char <i>port</i>)	procedure

Returns the next character available from the input *port*, updating the *port* to point to the following character. If no more characters are available, an end of file object is returned. *Port* may be omitted, in which case it defaults to the value returned by `current-input-port`.

(peek-char)	procedure
(peek-char <i>port</i>)	procedure

Returns the next character available from the input *port*, *without* updating the *port* to point to the following character. If no more characters are available, an end of file object is returned. *Port* may be omitted, in which case it defaults to the value returned by `current-input-port`.

Note: The value returned by a call to `peek-char` is the same as the value that would have been returned by a call to `read-char` with the same *port*. The only difference is that the very next call to `read-char` or `peek-char` on that *port* will return the value returned by the preceding call to `peek-char`. In particular, a call to `peek-char` on an interactive port will hang waiting for input whenever a call to `read-char` would have hung.

(eof-object? <i>obj</i>)	procedure
---------------------------	-----------

Returns `#t` if *obj* is an end of file object, otherwise returns `#f`. The precise set of end of file objects will vary among implementations, but in any case no end of file object will ever be an object that can be read in using `read`.

(char-ready?)	procedure
(char-ready? <i>port</i>)	procedure

Returns `#t` if a character is ready on the input *port* and returns `#t` otherwise. If `char-ready` returns `#t` then the next `read-char` operation on the given *port* is guaranteed not to hang. If the *port* is at end of file then `char-ready?` returns `#t`. *Port* may be omitted, in which case it defaults to the value returned by `current-input-port`.

Rationale: `Char-ready?` exists to make it possible for a program to accept characters from interactive ports without getting stuck waiting for input. Any input editors associated with such ports must ensure that characters whose existence has been asserted by `Char-ready?` cannot be rubbed out. If `Char-ready?` were to return `#f` at end of file, a port at end of file would be indistinguishable from an interactive port that has no ready characters.

7.6.3. Output.

<code>(write obj)</code>	library procedure
<code>(write obj port)</code>	library procedure

Writes a written representation of *obj* to the given *port*. Strings that appear in the written representation are enclosed in doublequotes, and within those strings backslash and doublequote characters are escaped by backslashes. Character objects are written using the `#\` notation. `Write` returns an unspecified value. The *port* argument may be omitted, in which case it defaults to the value returned by `current-output-port`.

<code>(display obj)</code>	library procedure
<code>(display obj port)</code>	library procedure

Writes a representation of *obj* to the given *port*. Strings that appear in the written representation are not enclosed in doublequotes, and no characters are escaped within those strings. Character objects appear in the representation as if written by `write-char` instead of by `write`. `Display` returns an unspecified value. The *port* argument may be omitted, in which case it defaults to the value returned by `current-output-port`.

Rationale: `Write` is intended for producing machine-readable output and `display` is for producing human-readable output. Implementations that allow “slashification” within symbols will probably want `write` but not `display` to slashify funny characters in symbols.

<code>(newline)</code>	library procedure
<code>(newline port)</code>	library procedure

Writes an end of line to *port*. Exactly how this is done differs from one operating system to another. Returns an unspecified value. The *port* argument may be omitted, in which case it defaults to the value returned by `current-output-port`.

<code>(write-char char)</code>	procedure
<code>(write-char char port)</code>	procedure

Writes the character *char* (not an external representation of the character) to the given *port* and returns an unspecified value. The *port* argument may be omitted, in which case it defaults to the value returned by `current-output-port`.

7.6.4. System interface. Questions of system interface generally fall outside of the domain of this report. However, the following operations are important enough to deserve description here.

`(load filename)` optional procedure

Filename should be a string naming an existing file containing Scheme source code. The `load` procedure reads expressions and definitions from the file and evaluates them sequentially. It is unspecified whether the results of the expressions are printed. The `load` procedure does not affect the values returned by `current-input-port` and `current-output-port`. `load` returns an unspecified value.

Rationale: For portability, `load` must operate on source files. Its operation on other kinds of files necessarily varies among implementations.

`(transcript-on filename)` optional procedure

`(transcript-off)` optional procedure

Filename must be a string naming an output file to be created. The effect of `transcript-on` is to open the named file for output, and to cause a transcript of subsequent interaction between the user and the Scheme system to be written to the file. The transcript is ended by a call to `transcript-off`, which closes the transcript file. Only one transcript may be in progress at any time, though some implementations may relax this restriction. The values returned by these procedures are unspecified.

8. Formal syntax and semantics

This chapter provides formal descriptions of what has already been described informally in previous sections of this report.

8.1. Formal syntax

This section provides a formal syntax for Scheme written in an extended BNF.

All spaces in the grammar are for legibility. Case is insignificant; for example, `#x1A` and `#X1a` are equivalent. `(empty)` stands for the empty string.

The following extensions to BNF are used to make the description more concise: $\langle \text{thing} \rangle^*$ means zero or more occurrences of $\langle \text{thing} \rangle$; and $\langle \text{thing} \rangle^+$ means at least one $\langle \text{thing} \rangle$.

8.1.1. Lexical structure. This section describes how individual tokens (identifiers, numbers, etc.) are formed from sequences of characters. The following sections describe how

expressions and programs are formed from sequences of tokens. ⟨Intertoken space⟩ may occur on either side of any token, but not within a token.

Tokens which require implicit termination (identifiers, numbers, characters, and dot) may be terminated by any ⟨delimiter⟩, but not necessarily by anything else.

The following five characters are reserved for future extensions to the language: [] { } |

⟨token⟩ → ⟨identifier⟩ | ⟨boolean⟩ | ⟨number⟩
 | ⟨character⟩ | ⟨string⟩
 | (|) | # (| ' | ` | , | , @ | .

⟨delimiter⟩ → ⟨whitespace⟩ | (|) | " | ;

⟨whitespace⟩ → ⟨space or newline⟩

⟨comment⟩ → ; ⟨all subsequent characters up to a
 line break⟩

⟨atmosphere⟩ → ⟨whitespace⟩ | ⟨comment⟩

⟨intertoken space⟩ → ⟨atmosphere⟩*

⟨identifier⟩ → ⟨initial⟩ ⟨subsequent⟩*
 | ⟨peculiar identifier⟩

⟨initial⟩ → ⟨letter⟩ | ⟨special initial⟩

⟨letter⟩ → a | b | c | ... | z

⟨special initial⟩ → ! | \$ | % | & | * | / | : | < | =
 | > | ? | ^ | _ | ~

⟨subsequent⟩ → ⟨initial⟩ | ⟨digit⟩
 | ⟨special subsequent⟩

⟨digit⟩ → 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

⟨special subsequent⟩ → + | - | . | @

⟨peculiar identifier⟩ → + | - | ...

⟨syntactic keyword⟩ → ⟨expression keyword⟩

| else | => | define

| unquote | unquote-splicing

⟨expression keyword⟩ → quote | lambda | if

| set! | begin | cond | and | or | case

| let | let* | letrec | do | delay

| quasiquote

⟨variable⟩ → ⟨any ⟨identifier⟩ that isn't
 also a ⟨syntactic keyword⟩⟩

⟨boolean⟩ → #t | #f

⟨character⟩ → #\ ⟨any character⟩
 | #\ ⟨character name⟩

⟨character name⟩ → space | newline

⟨string⟩ → " ⟨string element⟩* "

$\langle \text{string element} \rangle \longrightarrow \langle \text{any character other than " or } \backslash \rangle$
 $\quad | \backslash " | \backslash \backslash$

$\langle \text{number} \rangle \longrightarrow \langle \text{num } 2 \rangle | \langle \text{num } 8 \rangle$
 $\quad | \langle \text{num } 10 \rangle | \langle \text{num } 16 \rangle$

The following rules for $\langle \text{num } R \rangle$, $\langle \text{complex } R \rangle$, $\langle \text{real } R \rangle$, $\langle \text{ureal } R \rangle$, $\langle \text{uinteger } R \rangle$, and $\langle \text{prefix } R \rangle$ should be replicated for $R = 2, 8, 10$, and 16 . There are no rules for $\langle \text{decimal } 2 \rangle$, $\langle \text{decimal } 8 \rangle$, and $\langle \text{decimal } 16 \rangle$, which means that numbers containing decimal points or exponents must be in decimal radix.

$\langle \text{num } R \rangle \longrightarrow \langle \text{prefix } R \rangle \langle \text{complex } R \rangle$
 $\langle \text{complex } R \rangle \longrightarrow \langle \text{real } R \rangle | \langle \text{real } R \rangle @ \langle \text{real } R \rangle$
 $\quad | \langle \text{real } R \rangle + \langle \text{ureal } R \rangle i | \langle \text{real } R \rangle - \langle \text{ureal } R \rangle i$
 $\quad | \langle \text{real } R \rangle + i | \langle \text{real } R \rangle - i$
 $\quad | + \langle \text{ureal } R \rangle i | - \langle \text{ureal } R \rangle i | + i | - i$
 $\langle \text{real } R \rangle \longrightarrow \langle \text{sign} \rangle \langle \text{ureal } R \rangle$
 $\langle \text{ureal } R \rangle \longrightarrow \langle \text{uinteger } R \rangle$
 $\quad | \langle \text{uinteger } R \rangle / \langle \text{uinteger } R \rangle$
 $\quad | \langle \text{decimal } R \rangle$
 $\langle \text{decimal } 10 \rangle \longrightarrow \langle \text{uinteger } 10 \rangle \langle \text{suffix} \rangle$
 $\quad | . \langle \text{digit } 10 \rangle^+ \#^* \langle \text{suffix} \rangle$
 $\quad | \langle \text{digit } 10 \rangle^+ . \langle \text{digit } 10 \rangle^* \#^* \langle \text{suffix} \rangle$
 $\quad | \langle \text{digit } 10 \rangle^+ \#^+ . \#^* \langle \text{suffix} \rangle$
 $\langle \text{uinteger } R \rangle \longrightarrow \langle \text{digit } R \rangle^+ \#^*$
 $\langle \text{prefix } R \rangle \longrightarrow \langle \text{radix } R \rangle \langle \text{exactness} \rangle$
 $\quad | \langle \text{exactness} \rangle \langle \text{radix } R \rangle$

$\langle \text{suffix} \rangle \longrightarrow \langle \text{empty} \rangle$
 $\quad | \langle \text{exponent marker} \rangle \langle \text{sign} \rangle \langle \text{digit } 10 \rangle^+$
 $\langle \text{exponent marker} \rangle \longrightarrow e | s | f | d | l$
 $\langle \text{sign} \rangle \longrightarrow \langle \text{empty} \rangle | + | -$
 $\langle \text{exactness} \rangle \longrightarrow \langle \text{empty} \rangle | \#i | \#e$
 $\langle \text{radix } 2 \rangle \longrightarrow \#b$
 $\langle \text{radix } 8 \rangle \longrightarrow \#o$
 $\langle \text{radix } 10 \rangle \longrightarrow \langle \text{empty} \rangle | \#d$
 $\langle \text{radix } 16 \rangle \longrightarrow \#x$
 $\langle \text{digit } 2 \rangle \longrightarrow 0 | 1$
 $\langle \text{digit } 8 \rangle \longrightarrow 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7$
 $\langle \text{digit } 10 \rangle \longrightarrow \langle \text{digit} \rangle$
 $\langle \text{digit } 16 \rangle \longrightarrow \langle \text{digit } 10 \rangle | a | b | c | d | e | f$

8.1.2. External representations. $\langle \text{Datum} \rangle$ is what the read procedure (Section 7.6.2) successfully parses. Note that any string that parses as an $\langle \text{expression} \rangle$ will also parse as a $\langle \text{datum} \rangle$.

⟨datum⟩ → ⟨simple datum⟩ | ⟨compound datum⟩
 ⟨simple datum⟩ → ⟨boolean⟩ | ⟨number⟩
 | ⟨character⟩ | ⟨string⟩ | ⟨symbol⟩
 ⟨symbol⟩ → ⟨identifier⟩
 ⟨compound datum⟩ → ⟨list⟩ | ⟨vector⟩
 ⟨list⟩ → ((datum)*) | ((datum)⁺ . (datum))
 | ⟨abbreviation⟩
 ⟨abbreviation⟩ → ⟨abbrev prefix⟩ ⟨datum⟩
 ⟨abbrev prefix⟩ → ' | ` | , | , @
 ⟨vector⟩ → #((datum)*)

8.1.3. Expressions.

⟨expression⟩ → ⟨variable⟩
 | ⟨literal⟩
 | ⟨procedure call⟩
 | ⟨lambda expression⟩
 | ⟨conditional⟩
 | ⟨assignment⟩
 | ⟨derived expression⟩
 | ⟨macro use⟩
 | ⟨macro block⟩

⟨literal⟩ → ⟨quotation⟩ | ⟨self-evaluating⟩
 ⟨self-evaluating⟩ → ⟨boolean⟩ | ⟨number⟩
 | ⟨character⟩ | ⟨string⟩
 ⟨quotation⟩ → '⟨datum⟩ | (quote ⟨datum⟩)
 ⟨procedure call⟩ → ((operator) (operand)*)
 ⟨operator⟩ → ⟨expression⟩
 ⟨operand⟩ → ⟨expression⟩
 ⟨lambda expression⟩ → (lambda ⟨formals⟩ ⟨body⟩)
 ⟨formals⟩ → ((variable)*) | ⟨variable⟩
 | ((variable)⁺ . ⟨variable⟩)
 ⟨body⟩ → ⟨definition⟩* ⟨sequence⟩
 ⟨sequence⟩ → ⟨command⟩* ⟨expression⟩
 ⟨command⟩ → ⟨expression⟩

⟨conditional⟩ → (if ⟨test⟩ ⟨consequent⟩ ⟨alternate⟩)
 ⟨test⟩ → ⟨expression⟩
 ⟨consequent⟩ → ⟨expression⟩
 ⟨alternate⟩ → ⟨expression⟩ | ⟨empty⟩

⟨assignment⟩ → (set! ⟨variable⟩ ⟨expression⟩)

```

⟨derived expression⟩ →
  (cond ⟨cond clause⟩+)
  | (cond ⟨cond clause⟩* (else ⟨sequence⟩))
  | (case ⟨expression⟩
      ⟨case clause⟩+)
  | (case ⟨expression⟩
      ⟨case clause⟩*
      (else ⟨sequence⟩))
  | (and ⟨test⟩*)
  | (or ⟨test⟩*)
  | (let (⟨binding spec⟩*) ⟨body⟩)
  | (let ⟨variable⟩ (⟨binding spec⟩*) ⟨body⟩)
  | (let* (⟨binding spec⟩*) ⟨body⟩)
  | (letrec (⟨binding spec⟩*) ⟨body⟩)
  | (begin ⟨sequence⟩)
  | (do (⟨iteration spec⟩*)
        (⟨test⟩ ⟨do result⟩)
        ⟨command⟩*)
  | (delay ⟨expression⟩)
  | ⟨quasiquote⟩

⟨cond clause⟩ → (⟨test⟩ ⟨sequence⟩)
  | (⟨test⟩)
  | (⟨test⟩ => ⟨recipient⟩)
⟨recipient⟩ → ⟨expression⟩
⟨case clause⟩ → ((⟨datum⟩*) ⟨sequence⟩)
⟨binding spec⟩ → (⟨variable⟩ ⟨expression⟩)
⟨iteration spec⟩ → (⟨variable⟩ ⟨init⟩ ⟨step⟩)
  | (⟨variable⟩ ⟨init⟩)
⟨init⟩ → ⟨expression⟩
⟨step⟩ → ⟨expression⟩
⟨do result⟩ → ⟨sequence⟩ | ⟨empty⟩

⟨macro use⟩ → (⟨keyword⟩ ⟨datum⟩*)
⟨keyword⟩ → ⟨identifier⟩

⟨macro block⟩ →
  (let-syntax (⟨syntax spec⟩*) ⟨body⟩)
  | (letrec-syntax (⟨syntax spec⟩*) ⟨body⟩)
⟨syntax spec⟩ → (⟨keyword⟩ ⟨transformer spec⟩)

```

8.1.4. Quasiquote expressions. The following grammar for quasiquote expressions is not context-free. It is presented as a recipe for generating an infinite number of production rules. Imagine a copy of the following rules for $D = 1, 2, 3, \dots$. D keeps track of the nesting depth.

⟨quasiquote⟩ → ⟨quasiquote 1⟩
 ⟨qq template 0⟩ → ⟨expression⟩
 ⟨quasiquote D ⟩ → `⟨qq template D ⟩
 | ⟨quasiquote ⟨qq template D ⟩⟩
 ⟨qq template D ⟩ → ⟨simple datum⟩
 | ⟨list qq template D ⟩
 | ⟨vector qq template D ⟩
 | ⟨unquote D ⟩
 ⟨list qq template D ⟩ → (⟨qq template or splice D ⟩*)
 | (⟨qq template or splice D ⟩⁺ . ⟨qq template D ⟩)
 | '⟨qq template D ⟩
 | ⟨quasiquote $D + 1$ ⟩
 ⟨vector qq template D ⟩ → #⟨qq template or splice D ⟩*
 ⟨unquote D ⟩ → ,⟨qq template $D - 1$ ⟩
 | ⟨unquote ⟨qq template $D - 1$ ⟩⟩
 ⟨qq template or splice D ⟩ → ⟨qq template D ⟩
 | ⟨splicing unquote D ⟩
 ⟨splicing unquote D ⟩ → ,@⟨qq template $D - 1$ ⟩
 | ⟨unquote-splicing ⟨qq template $D - 1$ ⟩⟩

In ⟨quasiquote⟩s, a ⟨list qq template D ⟩ can sometimes be confused with either an ⟨unquote D ⟩ or a ⟨splicing unquote D ⟩. The interpretation as an ⟨unquote⟩ or ⟨splicing unquote D ⟩ takes precedence.

8.1.5. Transformers.

⟨transformer spec⟩ →
 ⟨syntax-rules (⟨identifier⟩*) ⟨syntax rule⟩*)
 ⟨syntax rule⟩ → (⟨pattern⟩ ⟨template⟩)
 ⟨pattern⟩ → ⟨pattern identifier⟩
 | (⟨pattern⟩*)
 | (⟨pattern⟩⁺ . ⟨pattern⟩)
 | (⟨pattern⟩* ⟨pattern⟩ ⟨ellipsis⟩)
 | #⟨pattern⟩*
 | #⟨pattern⟩* ⟨pattern⟩ ⟨ellipsis⟩
 | ⟨pattern datum⟩
 ⟨pattern datum⟩ → ⟨string⟩
 | ⟨character⟩
 | ⟨boolean⟩
 | ⟨number⟩
 ⟨template⟩ → ⟨pattern identifier⟩
 | (⟨template element⟩*)
 | (⟨template element⟩⁺ . ⟨template⟩)
 | #⟨template element⟩*
 | ⟨template datum⟩

$\langle \text{template element} \rangle \longrightarrow \langle \text{template} \rangle$
 | $\langle \text{template} \rangle \langle \text{ellipsis} \rangle$
 $\langle \text{template datum} \rangle \longrightarrow \langle \text{pattern datum} \rangle$
 $\langle \text{pattern identifier} \rangle \longrightarrow \langle \text{any identifier except } \dots \rangle$
 $\langle \text{ellipsis} \rangle \longrightarrow \langle \text{the identifier } \dots \rangle$

8.1.6. Programs and definitions.

$\langle \text{program} \rangle \longrightarrow \langle \text{command or definition} \rangle^*$
 $\langle \text{command or definition} \rangle \longrightarrow \langle \text{command} \rangle$
 | $\langle \text{definition} \rangle$
 | $\langle \text{syntax definition} \rangle$
 | $\langle \text{begin} \langle \text{command or definition} \rangle^+ \rangle$
 $\langle \text{definition} \rangle \longrightarrow \langle \text{define} \langle \text{variable} \rangle \langle \text{expression} \rangle \rangle$
 | $\langle \text{define} (\langle \text{variable} \rangle \langle \text{def formal} \rangle) \langle \text{body} \rangle \rangle$
 | $\langle \text{begin} \langle \text{definition} \rangle^* \rangle$
 $\langle \text{def formal} \rangle \longrightarrow \langle \text{variable} \rangle^*$
 | $\langle \text{variable} \rangle^* . \langle \text{variable} \rangle$
 $\langle \text{syntax definition} \rangle \longrightarrow$
 $\langle \text{define-syntax} \langle \text{keyword} \rangle \langle \text{transformer spec} \rangle \rangle$

8.2. Formal semantics

This section provides a formal denotational semantics for the primitive expressions of Scheme and selected built-in procedures. The concepts and notation used here are described in [29]; the notation is summarized below:

$\langle \dots \rangle$	sequence formation
$s \downarrow k$	k th member of the sequence s (1-based)
$\#s$	length of sequence s
$s \S t$	concatenation of sequences s and t
$s \dagger k$	drop the first k members of sequence s
$t \rightarrow a, b$	McCarthy conditional “if t then a else b ”
$\rho[x/i]$	substitution “ ρ with x for i ”
$x \text{ in } D$	injection of x into domain D
$x D$	projection of x to domain D

The reason that expression continuations take sequences of values instead of single values is to simplify the formal treatment of procedure calls and multiple return values.

The boolean flag associated with pairs, vectors, and strings will be true for mutable objects and false for immutable objects.

The order of evaluation within a call is unspecified. We mimic that here by applying arbitrary permutations *permute* and *unpermute*, which must be inverses, to the arguments in a call before and after they are evaluated. This is not quite right since it suggests,

incorrectly, that the order of evaluation is constant throughout a program (for any given number of arguments), but it is a closer approximation to the intended semantics than a left-to-right evaluation would be.

The storage allocator *new* is implementation-dependent, but it must obey the following axiom: if $new \sigma \in L$, then $\sigma(new \sigma \mid L) \downarrow 2 = false$.

The definition of \mathcal{K} is omitted because an accurate definition of \mathcal{K} would complicate the semantics without being very interesting.

If P is a program in which all variables are defined before being referenced or assigned, then the meaning of P is

$$\mathcal{E}[\langle (\lambda (I^*) P') \langle undefined \rangle \dots \rangle]$$

where I^* is the sequence of variables defined in P, P' is the sequence of expressions obtained by replacing every definition in P by an assignment, $\langle undefined \rangle$ is an expression that evaluates to *undefined*, and \mathcal{E} is the semantic function that assigns meaning to expressions.

8.2.1. Abstract syntax.

$K \in \text{Con}$	constants, including quotations
$I \in \text{Ide}$	identifiers (variables)
$E \in \text{Exp}$	expressions
$\Gamma \in \text{Com} = \text{Exp}$	commands

$$\begin{aligned} \text{Exp} \longrightarrow & K \mid I \mid (E_0 E^*) \\ & \mid (\lambda (I^*) \Gamma^* E_0) \\ & \mid (\lambda (I^* . I) \Gamma^* E_0) \\ & \mid (\lambda I \Gamma^* E_0) \\ & \mid (\text{if } E_0 E_1 E_2) \mid (\text{if } E_0 E_1) \\ & \mid (\text{set! } I E) \end{aligned}$$

8.2.2. Domain equations.

$\alpha \in L$	locations
$\nu \in \mathbb{N}$	natural numbers
$T = \{false, true\}$	booleans
Q	symbols
H	characters
R	numbers
$E_p = L \times L \times T$	pairs
$E_v = L^* \times T$	vectors
$E_s = L^* \times T$	strings
$M = \{false, true, null, undefined, unspecified\}$	miscellaneous
$\phi \in F = L \times (E^* \rightarrow K \rightarrow C)$	procedure values
$\epsilon \in E = Q + H + R + E_p + E_v + E_s + M + F$	expressed values

$\sigma \in \mathbf{S} = \mathbf{L} \rightarrow (\mathbf{E} \times \mathbf{T})$	stores
$\rho \in \mathbf{U} = \mathbf{Ide} \rightarrow \mathbf{L}$	environments
$\theta \in \mathbf{C} = \mathbf{S} \rightarrow \mathbf{A}$	command continuations
$\kappa \in \mathbf{K} = \mathbf{E}^* \rightarrow \mathbf{C}$	expression continuations
\mathbf{A}	answers
\mathbf{X}	errors

8.2.3. Semantic functions.

$\mathcal{K} : \mathbf{Con} \rightarrow \mathbf{E}$
$\mathcal{E} : \mathbf{Exp} \rightarrow \mathbf{U} \rightarrow \mathbf{K} \rightarrow \mathbf{C}$
$\mathcal{E}^* : \mathbf{Exp}^* \rightarrow \mathbf{U} \rightarrow \mathbf{K} \rightarrow \mathbf{C}$
$\mathcal{C} : \mathbf{Com}^* \rightarrow \mathbf{U} \rightarrow \mathbf{C} \rightarrow \mathbf{C}$

Definition of \mathcal{K} deliberately omitted.

$$\mathcal{E}[\mathbf{K}] = \lambda \rho \kappa . \text{send} (\mathcal{K}[\mathbf{K}]) \kappa$$

$$\begin{aligned} \mathcal{E}[\mathbf{I}] = \lambda \rho \kappa . \text{hold} (\text{lookup } \rho \mathbf{I}) \\ (\text{single}(\lambda \epsilon . \epsilon = \text{undefined} \rightarrow \\ \text{wrong} \text{ “undefined variable”,} \\ \text{send } \epsilon \kappa)) \end{aligned}$$

$$\begin{aligned} \mathcal{E}[(\mathbf{E}_0 \mathbf{E}^*)] = \\ \lambda \rho \kappa . \mathcal{E}^*(\text{permute}(\langle \mathbf{E}_0 \rangle \S \mathbf{E}^*)) \\ \rho \\ (\lambda \epsilon^* . ((\lambda \epsilon^* . \text{apply}(\epsilon^* \downarrow 1) (\epsilon^* \uparrow 1) \kappa) \\ (\text{unpermute } \epsilon^*))) \end{aligned}$$

$$\begin{aligned} \mathcal{E}[(\text{lambda } (\mathbf{I}^*) \Gamma^* \mathbf{E}_0)] = \\ \lambda \rho \kappa . \lambda \sigma . \\ \text{new } \sigma \in \mathbf{L} \rightarrow \\ \text{send} (\langle \text{new } \sigma \mid \mathbf{L}, \\ \lambda \epsilon^* \kappa' . \# \epsilon^* = \# \mathbf{I}^* \rightarrow \\ \text{tievals} (\lambda \alpha^* . (\lambda \rho' . \mathcal{C}[\Gamma^*] \rho' (\mathcal{E}[\mathbf{E}_0] \rho' \kappa')) \\ (\text{extends } \rho \mathbf{I}^* \alpha^*)) \\ \epsilon^*, \\ \text{wrong} \text{ “wrong number of arguments”}) \\ \text{in } \mathbf{E}) \\ \kappa \\ (\text{update} (\text{new } \sigma \mid \mathbf{L}) \text{unspecified } \sigma), \\ \text{wrong} \text{ “out of memory” } \sigma \end{aligned}$$

$$\begin{aligned} \mathcal{E}[(\text{lambda } (\mathbf{I}^* . \mathbf{I}) \Gamma^* \mathbf{E}_0)] = \\ \lambda \rho \kappa . \lambda \sigma . \end{aligned}$$

$new \sigma \in L \rightarrow$
 $send (\langle new \sigma \mid L,$
 $\lambda \epsilon^* \kappa' . \# \epsilon^* \geq \# I \rightarrow$
 $tievalsrest$
 $(\lambda \alpha^* . (\lambda \rho' . \mathcal{C}[\Gamma^*] \rho' (\mathcal{E}[\mathbb{E}_0] \rho' \kappa'))$
 $(extends \rho (I^* \S \langle I \rangle \alpha^*))$
 ϵ^*
 $(\# I^*),$
 $wrong \text{ “too few arguments”} \text{ in } E)$
 κ
 $(update (new \sigma \mid L) unspecified \sigma),$
 $wrong \text{ “out of memory” } \sigma$

$$\mathcal{E}[\langle \lambda \text{ambda } I \Gamma^* E_0 \rangle] = \mathcal{E}[\langle \lambda \text{ambda } (. I) \Gamma^* E_0 \rangle]$$

$$\mathcal{E}[\langle \text{if } E_0 E_1 E_2 \rangle] =$$

$$\lambda \rho \kappa . \mathcal{E}[\mathbb{E}_0] \rho (single(\lambda \epsilon . \text{truish } \epsilon \rightarrow \mathcal{E}[\mathbb{E}_1] \rho \kappa,$$

$$\mathcal{E}[\mathbb{E}_2] \rho \kappa))$$

$$\mathcal{E}[\langle \text{if } E_0 E_1 \rangle] =$$

$$\lambda \rho \kappa . \mathcal{E}[\mathbb{E}_0] \rho (single(\lambda \epsilon . \text{truish } \epsilon \rightarrow \mathcal{E}[\mathbb{E}_1] \rho \kappa,$$

$$send \text{ unspecified } \kappa))$$

Here and elsewhere, any expressed value other than *undefined* may be used in place of *unspecified*.

$$\mathcal{E}[\langle \text{set! } I E \rangle] =$$

$$\lambda \rho \kappa . \mathcal{E}[E] \rho (single(\lambda \epsilon . \text{assign}(\text{lookup } \rho I)$$

$$\epsilon$$

$$(send \text{ unspecified } \kappa)))$$

$$\mathcal{E}^*[\langle \rangle] = \lambda \rho \kappa . \kappa \langle \rangle$$

$$\mathcal{E}^*[\langle \mathbb{E}_0 \mathbb{E}^* \rangle] =$$

$$\lambda \rho \kappa . \mathcal{E}[\mathbb{E}_0] \rho (single(\lambda \epsilon_0 . \mathcal{E}^*[\mathbb{E}^*] \rho (\lambda \epsilon^* . \kappa ((\epsilon_0) \S \epsilon^*))))$$

$$\mathcal{C}[\langle \rangle] = \lambda \rho \theta . \theta$$

$$\mathcal{C}[\langle \Gamma_0 \Gamma^* \rangle] = \lambda \rho \theta . \mathcal{E}[\Gamma_0] \rho (\lambda \epsilon^* . \mathcal{C}[\Gamma^*] \rho \theta)$$

8.2.4. Auxiliary functions.

$lookup : U \rightarrow \text{Ide} \rightarrow L$

$lookup = \lambda \rho I . \rho I$

extends : $U \rightarrow \text{Ide}^* \rightarrow L^* \rightarrow U$

extends =

$$\lambda \rho I^* \alpha^* . \#I^* = 0 \rightarrow \rho, \\ \text{extends } (\rho[(\alpha^* \downarrow 1)/(I^* \downarrow 1)]) (I^* \dagger 1) (\alpha^* \dagger 1)$$

wrong : $X \rightarrow C$ [implementation-dependent]

send : $E \rightarrow K \rightarrow C$

send = $\lambda \epsilon \kappa . \kappa \langle \epsilon \rangle$

single : $(E \rightarrow C) \rightarrow K$

single =

$$\lambda \psi \epsilon^* . \# \epsilon^* = 1 \rightarrow \psi(\epsilon^* \downarrow 1), \\ \text{wrong "wrong number of return values"}$$

new : $S \rightarrow (L + \{\text{error}\})$ [implementation-dependent]

hold : $L \rightarrow K \rightarrow C$

hold = $\lambda \alpha \kappa \sigma . \text{send } (\sigma \alpha \downarrow 1) \kappa \sigma$

assign : $L \rightarrow E \rightarrow C \rightarrow C$

assign = $\lambda \alpha \epsilon \theta \sigma . \theta(\text{update } \alpha \epsilon \sigma)$

update : $L \rightarrow E \rightarrow S \rightarrow S$

update = $\lambda \alpha \epsilon \sigma . \sigma[(\epsilon, \text{true})/\alpha]$

tievals : $(L^* \rightarrow C) \rightarrow E^* \rightarrow C$

tievals =

$$\lambda \psi \epsilon^* \sigma . \# \epsilon^* = 0 \rightarrow \psi \langle \rangle \sigma, \\ \text{new } \sigma \in L \rightarrow \text{tievals } (\lambda \alpha^* . \psi \langle (\text{new } \sigma \mid L) \S \alpha^* \rangle \\ (\epsilon^* \dagger 1) \\ (\text{update}(\text{new } \sigma \mid L)(\epsilon^* \downarrow 1)\sigma), \\ \text{wrong "out of memory"} \sigma$$

tievalsrest : $(L^* \rightarrow C) \rightarrow E^* \rightarrow N \rightarrow C$

tievalsrest =

$$\lambda \psi \epsilon^* v . \text{list } (\text{dropfirst } \epsilon^* v) \\ (\text{single}(\lambda \epsilon . \text{tievals } \psi \langle (\text{takefirst } \epsilon^* v) \S \langle \epsilon \rangle \rangle))$$

dropfirst = $\lambda l n . n = 0 \rightarrow l, \text{dropfirst } (l \dagger 1)(n - 1)$

takefirst = $\lambda l n . n = 0 \rightarrow \langle \rangle, \langle l \downarrow 1 \rangle \S (\text{takefirst } (l \dagger 1)(n - 1))$

truish : $E \rightarrow T$

truish = $\lambda \epsilon . \epsilon = \text{false} \rightarrow \text{false}, \text{true}$

permute : $\text{Exp}^* \rightarrow \text{Exp}^*$ [implementation-dependent]

unpermute : $\text{E}^* \rightarrow \text{E}^*$ [inverse of *permute*]

applicat : $\text{E} \rightarrow \text{E}^* \rightarrow \text{K} \rightarrow \text{C}$

applicat =

$\lambda \epsilon \in^* \kappa . \epsilon \in \text{F} \rightarrow (\epsilon \mid \text{F} \downarrow 2) \epsilon^* \kappa$, *wrong* “bad procedure”

onearg : $(\text{E} \rightarrow \text{K} \rightarrow \text{C}) \rightarrow (\text{E}^* \rightarrow \text{K} \rightarrow \text{C})$

onearg =

$\lambda \zeta \epsilon^* \kappa . \# \epsilon^* = 1 \rightarrow \zeta(\epsilon^* \downarrow 1) \kappa$,
wrong “wrong number of arguments”

twoarg : $(\text{E} \rightarrow \text{E} \rightarrow \text{K} \rightarrow \text{C}) \rightarrow (\text{E}^* \rightarrow \text{K} \rightarrow \text{C})$

twoarg =

$\lambda \zeta \epsilon^* \kappa . \# \epsilon^* = 2 \rightarrow \zeta(\epsilon^* \downarrow 1)(\epsilon^* \downarrow 2) \kappa$,
wrong “wrong number of arguments”

list : $\text{E}^* \rightarrow \text{K} \rightarrow \text{C}$

list =

$\lambda \epsilon^* \kappa . \# \epsilon^* = 0 \rightarrow \text{send null } \kappa$,
list $(\epsilon^* \dagger 1)(\text{single}(\lambda \epsilon . \text{cons}(\epsilon^* \downarrow 1, \epsilon) \kappa))$

cons : $\text{E}^* \rightarrow \text{K} \rightarrow \text{C}$

cons =

twoarg $(\lambda \epsilon_1 \epsilon_2 \kappa \sigma . \text{new } \sigma \in \text{L} \rightarrow$
 $(\lambda \sigma' . \text{new } \sigma' \in \text{L} \rightarrow$
 $\text{send } ((\text{new } \sigma \mid \text{L}, \text{new } \sigma' \mid \text{L}, \text{true})$
 $\text{in E})$
 κ
 $(\text{update}(\text{new } \sigma' \mid \text{L}) \epsilon_2 \sigma')$,
wrong “out of memory” σ')
 $(\text{update}(\text{new } \sigma \mid \text{L}) \epsilon_1 \sigma)$,
wrong “out of memory” σ)

less : $\text{E}^* \rightarrow \text{K} \rightarrow \text{C}$

less =

twoarg $(\lambda \epsilon_1 \epsilon_2 \kappa . (\epsilon_1 \in \text{R} \wedge \epsilon_2 \in \text{R}) \rightarrow$
 $\text{send } (\epsilon_1 \mid \text{R} < \epsilon_2 \mid \text{R} \rightarrow \text{true}, \text{false}) \kappa$,
wrong “non-numeric argument to <”)

add : $\text{E}^* \rightarrow \text{K} \rightarrow \text{C}$

add =

twoarg $(\lambda \epsilon_1 \epsilon_2 \kappa . (\epsilon_1 \in \text{R} \wedge \epsilon_2 \in \text{R}) \rightarrow$
 $\text{send } ((\epsilon_1 \mid \text{R} + \epsilon_2 \mid \text{R}) \text{ in E}) \kappa$,
wrong “non-numeric argument to +”)

$car : E^* \rightarrow K \rightarrow C$

$car =$

$onearg (\lambda \epsilon \kappa . \epsilon \in E_p \rightarrow hold (\epsilon \mid E_p \downarrow 1) \kappa,$
 $wrong \text{ “non-pair argument to car”})$

$cdr : E^* \rightarrow K \rightarrow C$ [similar to car]

$setcar : E^* \rightarrow K \rightarrow C$

$setcar =$

$twoarg (\lambda \epsilon_1 \epsilon_2 \kappa . \epsilon_1 \in E_p \rightarrow$
 $(\epsilon_1 \mid E_p \downarrow 3) \rightarrow assign (\epsilon_1 \mid E_p \downarrow 1)$
 ϵ_2
 $(send \text{ unspecified } \kappa),$
 $wrong \text{ “immutable argument to set-car!”},$
 $wrong \text{ “non-pair argument to set-car!”})$

$eqv : E^* \rightarrow K \rightarrow C$

$eqv =$

$twoarg (\lambda \epsilon_1 \epsilon_2 \kappa . (\epsilon_1 \in M \wedge \epsilon_2 \in M) \rightarrow$
 $send (\epsilon_1 \mid M = \epsilon_2 \mid M \rightarrow true, false) \kappa,$
 $(\epsilon_1 \in Q \wedge \epsilon_2 \in Q) \rightarrow$
 $send (\epsilon_1 \mid Q = \epsilon_2 \mid Q \rightarrow true, false) \kappa,$
 $(\epsilon_1 \in H \wedge \epsilon_2 \in H) \rightarrow$
 $send (\epsilon_1 \mid H = \epsilon_2 \mid H \rightarrow true, false) \kappa,$
 $(\epsilon_1 \in R \wedge \epsilon_2 \in R) \rightarrow$
 $send (\epsilon_1 \mid R = \epsilon_2 \mid R \rightarrow true, false) \kappa,$
 $(\epsilon_1 \in E_p \wedge \epsilon_2 \in E_p) \rightarrow$
 $send ((\lambda p_1 p_2 . ((p_1 \downarrow 1) = (p_2 \downarrow 1) \wedge$
 $(p_1 \downarrow 2) = (p_2 \downarrow 2)) \rightarrow true,$
 $false)$
 $(\epsilon_1 \mid E_p)$
 $(\epsilon_2 \mid E_p))$
 $\kappa,$
 $(\epsilon_1 \in E_v \wedge \epsilon_2 \in E_v) \rightarrow \dots,$
 $(\epsilon_1 \in E_s \wedge \epsilon_2 \in E_s) \rightarrow \dots,$
 $(\epsilon_1 \in F \wedge \epsilon_2 \in F) \rightarrow$
 $send ((\epsilon_1 \mid F \downarrow 1) = (\epsilon_2 \mid F \downarrow 1) \rightarrow true, false)$
 $\kappa,$
 $send \text{ false } \kappa)$

$apply : E^* \rightarrow K \rightarrow C$

$apply =$

$twoarg (\lambda \epsilon_1 \epsilon_2 \kappa . \epsilon_1 \in F \rightarrow valueslist (\epsilon_2) (\lambda \epsilon^* . applicate \epsilon_1 \epsilon^* \kappa),$
 $wrong \text{ “bad procedure argument to apply”})$

$valueslist : E^* \rightarrow K \rightarrow C$

valueslist =
onearg ($\lambda \epsilon \kappa . \epsilon \in E_p \rightarrow$
 $\text{cdr}(\epsilon)$
 $(\lambda \epsilon^* . \text{valueslist}$
 ϵ^*
 $(\lambda \epsilon^* . \text{car}(\epsilon)(\text{single}(\lambda \epsilon . \kappa((\epsilon) \S \epsilon^*))))$),
 $\epsilon = \text{null} \rightarrow \kappa \langle \rangle$,
wrong “non-list argument to values-list”)

cwcc : $E^* \rightarrow K \rightarrow C$ [call-with-current-continuation]

cwcc =
onearg ($\lambda \epsilon \kappa . \epsilon \in F \rightarrow$
 $(\lambda \sigma . \text{new } \sigma \in L \rightarrow$
apply ϵ
 $\langle \langle \text{new } \sigma \mid L, \lambda \epsilon^* \kappa' . \kappa \epsilon^* \rangle \text{ in } E \rangle$
 κ
 $(\text{update}(\text{new } \sigma \mid L)$
unspecified
 $\sigma)$,
wrong “out of memory” σ),
wrong “bad procedure argument”)

values : $E^* \rightarrow K \rightarrow C$

values = $\lambda \epsilon^* \kappa . \kappa \epsilon^*$

cwv : $E^* \rightarrow K \rightarrow C$ [call-with-values]

cwv =
twoarg ($\lambda \epsilon_1 \epsilon_2 \kappa . \text{apply} \epsilon_1 \langle \rangle (\lambda \epsilon^* . \text{apply} \epsilon_2 \epsilon^*)$)

8.3. Derived expression types

This section gives macro definitions for the derived expression types in terms of the primitive expression types (literal, variable, call, lambda, if, set!). See Section 7.4 for a possible definition of delay.

```

(define-syntax cond
  (syntax-rules (else =>)
    ((cond (else result1 result2 ...))
     (begin result1 result2 ...))
    ((cond (test => result))
     (let ((temp test))
       (if temp (result temp))))
    ((cond (test => result) clause1 clause2 ...))
    (let ((temp test))
      (if temp

```

```

        (result temp)
        (cond clause1 clause2 ...))))
((cond (test)) test)
((cond (test) clause1 clause2 ...)
 (let ((temp test))
  (if temp
   temp
   (cond clause1 clause2 ...))))
((cond (test result1 result2 ...)
 (if test (begin result1 result2 ...)))
((cond (test result1 result2 ...)
 clause1 clause2 ...)
 (if test
  (begin result1 result2 ...)
  (cond clause1 clause2 ...))))))

(define-syntax case
  (syntax-rules (else)
    ((case (key ...)
      clauses ...)
     (let ((atom-key (key ...)))
       (case atom-key clauses ...)))
    ((case key
      (else result1 result2 ...)
      (begin result1 result2 ...))
     ((case key
      ((atoms ...) result1 result2 ...)
      (if (memv key '(atoms ...))
          (begin result1 result2 ...)))
     ((case key
      ((atoms ...) result1 result2 ...)
      clause clauses ...)
      (if (memv key '(atoms ...))
          (begin result1 result2 ...)
          (case key clause clauses ...))))))

(define-syntax and
  (syntax-rules ()
    ((and) #t)
    ((and test) test)
    ((and test1 test2 ...)
     (if test1 (and test2 ...) #f))))

(define-syntax or
  (syntax-rules ()

```

```

((or) #f)
((or test) test)
((or test1 test2 ...)
 (let ((x test1))
   (if x x (or test2 ...))))))

(define-syntax let
  (syntax-rules ()
    ((let ((name val) ...) body1 body2 ...)
     ((lambda (name ...) body1 body2 ...)
      val ...))
    ((let tag ((name val) ...) body1 body2 ...)
     ((letrec ((tag (lambda (name ...)
                      body1 body2 ...)))
      tag)
      val ...))))

(define-syntax let*
  (syntax-rules ()
    ((let* () body1 body2 ...)
     (let () body1 body2 ...))
    ((let* ((name1 val1) (name2 val2) ...)
     body1 body2 ...)
     (let ((name1 val1))
       (let* ((name2 val2) ...)
         body1 body2 ...))))))

```

The following `letrec` macro uses the symbol `<undefined>` in place of an expression which returns something that when stored in a location makes it an error to try to obtain the value stored in the location (no such expression is defined in Scheme). A trick is used to generate the temporary names needed to avoid specifying the order in which the values are evaluated. This could also be accomplished by using an auxiliary macro.

```

(define-syntax letrec
  (syntax-rules ()
    ((letrec ((var1 init1) ...) body ...)
     (letrec "generate_temp_names"
       (var1 ...)
       ()
       ((var1 init1) ...)
       body ...))
    ((letrec "generate_temp_names"
     ()
     (temp1 ...))

```

```

      ((var1 init1) ...)
      body ...)
  (let ((var1 <undefined>) ...)
    (let ((temp1 init1) ...)
      (set! var1 temp1)
      ...
      body ...)))
  ((letrec "generate_temp_names"
    (x y ...)
    (temp ...)
    ((var1 init1) ...)
    body ...)
    (letrec "generate_temp_names"
      (y ...)
      (newtemp temp ...)
      ((var1 init1) ...)
      body ...))))

(define-syntax begin
  (syntax-rules ()
    ((begin exp ...)
     ((lambda () exp ...))))))

```

The following alternative expansion for `begin` does not make use of the ability to write more than one expression in the body of a lambda expression. In any case, note that these rules apply only if the body of the `begin` contains no definitions.

```

(define-syntax begin
  (syntax-rules ()
    ((begin exp)
     exp)
    ((begin exp1 exp2 ...)
     (let ((x exp1))
       (begin exp2 ...))))))

```

The following definition of `do` uses a trick to expand the variable clauses. As with `letrec` above, an auxiliary macro would also work. The expression `(if #f #f)` is used to obtain an unspecified value.

```

(define-syntax do
  (syntax-rules ()
    ((do ((var init step ...) ...)
         (test expr ...)
         command ...))

```

```

(letrec
  ((loop
    (lambda (var ...)
      (if test
        (begin
          (if #f #f)
          expr ...)
        (begin
          command
          ...
          (loop (do "step" var step ...)
                ...))))))
  (loop init ...))
((do "step" x)
 x)
((do "step" x y)
 y)))

```

Notes

Language changes. This section enumerates the changes that have been made to Scheme since the “Revised⁴ report” [6] was published.

- The report is now a superset of the IEEE standard for Scheme [13]: implementations that conform to the report will also conform to the standard. This required the following changes:
 - The empty list is now required to count as true.
 - The classification of features as essential or inessential has been removed. There are now three classes of built-in procedures: primitive, library, and optional. The optional procedures are `load`, `with-input-from-file`, `with-output-to-file`, `transcript-on`, `transcript-off`, and `interaction-environment`, and `-` and `/` with more than two arguments. None of these are in the IEEE standard.
 - Programs are allowed to redefine built-in procedures. Doing so will not change the behavior of other built-in procedures.
- *Port* has been added to the list of disjoint types.
- The macro appendix has been removed. High-level macros are now part of the main body of the report. The rewrite rules for derived expressions have been replaced with macro definitions. There are no reserved identifiers.
- `Syntax-rules` now allows vector patterns.
- Multiple-value returns, `eval`, and `dynamic-wind` have been added.
- The calls that are required to be implemented in a properly tail-recursive fashion are defined explicitly.
- ‘@’ can be used within identifiers. ‘|’ is reserved for possible future extensions.

Additional material

The Internet Scheme Repository at

<http://www.cs.indiana.edu/scheme-repository/>

contains an extensive Scheme bibliography, as well as papers, programs, implementations, and other material related to Scheme.

Example

`integrate-system` integrates the system

$$y'_k = f_k(y_1, y_2, \dots, y_n), \quad k = 1, \dots, n$$

of differential equations with the method of Runge-Kutta.

The parameter `system-derivative` is a function that takes a system state (a vector of values for the state variables y_1, \dots, y_n) and produces a system derivative (the values y'_1, \dots, y'_n). The parameter `initial-state` provides an initial system state, and `h` is an initial guess for the length of the integration step.

The value returned by `integrate-system` is an infinite stream of system states.

```
(define integrate-system
  (lambda (system-derivative initial-state h)
    (let ((next (runge-kutta-4 system-derivative h)))
      (letrec ((states
                 (cons initial-state
                       (delay (map-streams next
                                         states))))))
        states))))
```

`Runge-Kutta-4` takes a function, `f`, that produces a system derivative from a system state. `Runge-Kutta-4` produces a function that takes a system state and produces a new system state.

```
(define runge-kutta-4
  (lambda (f h)
    (let ((*h (scale-vector h))
          (*2 (scale-vector 2))
          (*1/2 (scale-vector (/ 1 2)))
          (*1/6 (scale-vector (/ 1 6))))
      (lambda (y)
        ;; y is a system state
        (let* ((k0 (*h (f y)))
```

```

      (k1 (*h (f (add-vectors y (*1/2 k0))))))
      (k2 (*h (f (add-vectors y (*1/2 k1))))))
      (k3 (*h (f (add-vectors y k2))))))
    (add-vectors y
      (*1/6 (add-vectors k0
                    (*2 k1)
                    (*2 k2)
                    k3))))))

(define elementwise
  (lambda (f)
    (lambda vectors
      (generate-vector
        (vector-length (car vectors))
        (lambda (i)
          (apply f
                 (map (lambda (v) (vector-ref v i))
                      vectors)))))))

(define generate-vector
  (lambda (size proc)
    (let ((ans (make-vector size)))
      (letrec ((loop
                 (lambda (i)
                   (cond ((= i size) ans)
                         (else
                          (vector-set! ans i (proc i))
                          (loop (+ i 1)))))))
        (loop 0))))))

(define add-vectors (elementwise +))

(define scale-vector
  (lambda (s)
    (elementwise (lambda (x) (* x s)))))

```

Map-streams is analogous to map: it applies its first argument (a procedure) to all the elements of its second argument (a stream).

```

(define map-streams
  (lambda (f s)
    (cons (f (head s))
          (delay (map-streams f (tail s))))))

```

Infinite streams are implemented as pairs whose car holds the first element of the stream and whose cdr holds a promise to deliver the rest of the stream.

```
(define head car)
(define tail
  (lambda (stream) (force (cdr stream))))
```

The following illustrates the use of `integrate-system` in integrating the system

$$C \frac{dv_C}{dt} = -i_L - \frac{v_C}{R}$$

$$L \frac{di_L}{dt} = v_C$$

which models a damped oscillator.

```
(define damped-oscillator
  (lambda (R L C)
    (lambda (state)
      (let ((Vc (vector-ref state 0))
            (Il (vector-ref state 1)))
        (vector (- 0 (+ (/ Vc (* R C)) (/ Il C)))
                (/ Vc L))))))

(define the-states
  (integrate-system
    (damped-oscillator 10000 1000 .001)
    '(#(1 0)
      .01))
```

Acknowledgments

We would like to thank the following people for their help: Alan Bawden, Michael Blair, George Carrette, Andy Cromarty, Pavel Curtis, Jeff Dalton, Olivier Danvy, Ken Dickey, Bruce Duba, Marc Feeley, Andy Freeman, Richard Gabriel, Yekta Gürsel, Ken Haase, Robert Hieb, Paul Hudak, Morry Katz, Chris Lindblad, Mark Meyer, Jim Miller, Jim Philbin, John Ramsdell, Mike Shaff, Jonathan Shapiro, Julie Sussman, Perry Wagle, Daniel Weise, Henry Wu, and Ozan Yigit. We thank Carol Fessenden, Daniel Friedman, and Christopher Haynes for permission to use text from the Scheme 311 version 4 reference manual. We thank Texas Instruments, Inc. for permission to use text from the *TI Scheme Language Reference Manual* [30]. We gladly acknowledge the influence of manuals for MIT Scheme [17], T [22], Scheme 84 [11], Common Lisp [27], and Algol 60 [18].

We also thank Betty Dexter for the extreme effort she put into setting this report in \TeX , and Donald Knuth for designing the program that caused her troubles.

The Artificial Intelligence Laboratory of the Massachusetts Institute of Technology, the Computer Science Department of Indiana University, the Computer and Information Sciences Department of the University of Oregon, and the NEC Research Institute supported the

preparation of this report. Support for the MIT work was provided in part by the Advanced Research Projects Agency of the Department of Defense under Office of Naval Research contract N00014-80-C-0505. Support for the Indiana University work was provided by NSF grants NCS 83-04567 and NCS 83-03325.

References

1. Abelson, Harold and Sussman, Gerald Jay with Sussman, Julie. *Structure and Interpretation of Computer Programs*, 2nd edition. MIT Press, Cambridge, 1996.
2. Bawden, Alan and Rees, Jonathan. Syntactic closures. In *Proceedings of the ACM Symposium on Lisp and Functional Programming*, 1988, pp. 86–95.
3. Burger, Robert G. and Dybvig, R. Kent. Printing floating-point numbers quickly and accurately. In *Proceedings of the ACM SIGPLAN Conference on Programming Language Design and Implementation*, 1996, pp. 108–116.
4. Clinger, William (Ed.). The revised report on Scheme, or an uncommon Lisp. MIT Artificial Intelligence Memo 848, Aug. 1985. Also published as Computer Science Department Technical Report 174, Indiana University, June 1985.
5. Clinger, William. How to read floating point numbers accurately. In *Proceedings of the ACM SIGPLAN Conference on Programming Language Design and Implementation*. Proceedings published as *SIGPLAN Notices* **25**(6): 92–101, June 1990.
6. Clinger, William and Rees, Jonathan (Eds.). The revised⁴ report on the algorithmic language Scheme. *ACM Lisp Pointers* **4**(3):1–55, 1991.
7. Clinger, William and Rees, Jonathan. Macros that work. In *Proceedings of the ACM Conference on Principles of Programming Languages*, 1991, pp. 155–162.
8. Clinger, William. Proper tail recursion and space efficiency. To appear in *Proceedings of the ACM Conference on Programming Language Design and Implementation*, June 1998.
9. Dybvig, R. Kent, Hieb, Robert, and Bruggeman, Carl. Syntactic abstraction in Scheme. *Lisp and Symbolic Computation* **5**(4):295–326, 1993.
10. Fessenden, Carol, Clinger, William, Friedman, Daniel P., and Haynes, Christopher. Scheme 311 version 4 reference manual. Indiana University Computer Science Technical Report 137, Feb. 1983. Superseded by [11].
11. Friedman, D., Haynes, C., Kohlbecker, E., and Wand, M. Scheme 84 interim reference manual. Indiana University Computer Science Technical Report 153, Jan. 1985.
12. *IEEE Standard 754-1985. IEEE Standard for Binary Floating-Point Arithmetic*. IEEE, New York, 1985.
13. *IEEE Standard 1178-1990. IEEE Standard for the Scheme Programming Language*. IEEE, New York, 1991.
14. Kohlbecker, Eugene E., Jr. Syntactic extensions in the programming language lisp. PhD thesis, Indiana University, Aug. 1986.
15. Kohlbecker, Eugene E., Jr., Friedman, Daniel P., Felleisen, Matthias, and Duba, Bruce. Hygienic macro expansion. In *Proceedings of the ACM Conference on Lisp and Functional Programming*, 1986, pp. 151–161.
16. Landin, Peter. A correspondence between Algol 60 and Church’s lambda notation: Part I. *Communications of the ACM* **8**(2): 89–101, Feb. 1965.
17. MIT Department of Electrical Engineering and Computer Science. Scheme manual, 7th edition. Sept. 1984.
18. Naur, Peter, et al. Revised report on the algorithmic language Algol 60. *Communications of the ACM* **6**(1):1–17, Jan. 1963.
19. Penfield, Paul, Jr. Principal values and branch cuts in complex APL. In *APL Conference Proceedings*, ACM SIGAPL, San Francisco. Proceedings published as *APL Quote Quad* **12**(1):248–256, ACM, Sept. 1981.
20. Pitman, Kent M. The revised MacLisp manual (Saturday evening edition). MIT Laboratory for Computer Science Technical Report 295, May 1983.
21. Rees, Jonathan A. and Adams IV, Norman I. T: A dialect of Lisp or, lambda: The ultimate software tool. In *Conference Record of the ACM Symposium on Lisp and Functional Programming*, 1982, pp. 114–122.
22. Rees, Jonathan A., Adams IV, Norman I, and Meehan, J.R. The T manual, 4th edition. Yale University Computer Science Department, Jan. 1984.
23. Rees, Jonathan and Clinger, William (Eds.). The revised³ report on the algorithmic language Scheme, *ACM SIGPLAN Notices* **21**(12):37–79, Dec. 1986.

24. Reynolds, John. Definitional interpreters for higher order programming languages. *ACM Conference Proceedings*, pp. 717–740, ACM, 1972.
25. Steele, Guy Lewis, Jr. and Sussman, Gerald Jay. The revised report on Scheme, a dialect of Lisp. MIT Artificial Intelligence Memo 452, Jan. 1978.
26. Steele, Guy Lewis, Jr. Rabbit: A compiler for Scheme. MIT Artificial Intelligence Laboratory Technical Report 474, May 1978.
27. Steele, Guy Lewis, Jr. *Common Lisp: The Language, second edition*. Digital Press, Burlington MA, 1990.
28. Sussman, Gerald Jay and Steele, Guy Lewis, Jr. Scheme: An interpreter for extended lambda calculus. MIT Artificial Intelligence Memo 349, Dec. 1975.
29. Stoy, Joseph E. *Denotational Semantics: The Scott-Strachey Approach to Programming Language Theory*, MIT Press, Cambridge, 1977.
30. Texas Instruments, Inc. TI Scheme Language Reference Manual. Preliminary version 1.0, Nov. 1985.

Alphabetic index of definitions of concepts, keywords, and procedures

The principal entry for each term, procedure, or keyword is listed first, separated from the other entries by a semicolon.

!	12	cadr	55
'	19; 54	call	20
*	46	call by need	28
+	46; 12, 89	call-with-current-continuation	70; 18, 72, 91
,	28; 54	call-with-input-file	74
,@	28	call-with-output-file	74
-	46; 12	call-with-values	72; 18, 71, 91
->	12	call/cc	71
...	12; 31	car	55; 90
/	46	case	23; 92
;	13	catch	71
<	45; 89	cdddar	55
<=	45	cddddr	55
=	45	cdr	55
=>	22; 23	ceiling	48
>	45	char->integer	61
>=	45	char-alphabetic?	61
?	12	char-ci<=?	61
'	28	char-ci<?	61
		char-ci=?	61
		char-ci>=?	61
		char-ci>?	61
abs	46; 50	char-downcase	62
acos	49	char-lower-case?	61
and	24; 92	char-numeric?	61
angle	50	char-ready?	76
append	56	char-upcase	62
apply	67; 18, 90	char-upper-case?	61
asin	49	char-whitespace?	61
assoc	58	char<=?	60; 62
assq	58	char<?	60
assv	58	char=?	60
atan	49	char>=?	60
		char>?	60
#b	43; 80	char?	60; 15
backquote	28	close-input-port	75
begin	26; 34, 35, 94	close-output-port	75
binding	14	combination	20
binding construct	14	comma	28
boolean?	52; 14		
bound	14		
caar	55		

comment 13; 79
 complex? 44; 41
 cond 22; 33, 91
 cons 54
 constant 16
 continuation 71
 cos 49
 current-input-port 75
 current-output-port 75

 #d 43
 define 34; 30
 define-syntax 35
 definition 34
 delay 28; 68
 denominator 48
 display 77
 do 26; 94
 dotted pair 53
 dynamic-wind 72; 70

 #e 43; 80
 else 22; 23
 empty list 53; 15, 52, 55, 56
 eof-object? 76
 eq? 39; 21
 equal? 40
 equivalence predicate 36
 eqv? 37; 16, 21, 90
 error 10
 escape procedure 70
 eval 73; 18
 even? 45
 exact 37
 exact->inexact 50
 exact? 45
 exactness 41
 exp 49
 expt 50

 #f 52
 false 15; 52
 floor 48
 for-each 67
 force 68; 28

 gcd 47

 hygienic 30

 #i 43; 80
 identifier 12; 14, 58, 79
 if 21; 87
 imag-part 50
 immutable 16
 implementation restriction
 10; 42
 improper list 53
 inexact 37
 inexact->exact 50; 42
 inexact? 45
 initial environment 35
 input-port? 75
 integer->char 61
 integer? 44; 41
 interaction-environment 74
 internal definition 35

 keyword 29; 79

 lambda 20; 35, 87
 lazy evaluation 28
 lcm 47
 length 56; 42
 let 24; 27, 33, 35, 93
 let* 25; 35, 93
 let-syntax 30; 35
 letrec 25; 35, 93
 letrec-syntax 30; 35
 library 10
 library procedure 36
 list 56
 list->string 64
 list->vector 66
 list-ref 57
 list-tail 57
 list? 56
 load 78
 location 15
 log 49

macro 29
macro keyword 29
macro transformer 29
macro use 29
magnitude 50
make-polar 50
make-rectangular 50
make-string 62
make-vector 65
map 67
max 45
member 57
memq 57
memv 57
min 45
modulo 46
mutable 16

negative? 45
newline 77
nil 52
not 52
null-environment 73
null? 56
number 40
number->string 51
number? 44; 14, 41, 44
numerator 48
numerical types 41

#o 43; 80
object 8
odd? 45
open-input-file 75
open-output-file 75
optional 9
or 24; 93
output-port? 75

pair 53
pair? 54; 14
peek-char 76
port 74
port? 15
positive? 45
predicate 36
procedure call 20
procedure? 66; 15

promise 28; 68
proper tail recursion 16

quasiquote 28; 29, 54
quote 19; 54
quotient 46

rational? 44; 41
rationalize 48
read 76; 54, 80
read-char 76
real-part 50
real? 44; 41, 44
referentially transparent 30
region 14; 22, 24, 25, 27
remainder 46
reverse 57
round 48

scheme-report-environment 74
set! 22; 34, 87
set-car! 55
set-cdr! 55; 54
setcar 90
simplest rational 49
sin 49
sqrt 49
string 63
string->list 64
string->number 51
string->symbol 59
string-append 64
string-ci<=? 63
string-ci<? 63
string-ci=? 63
string-ci>=? 63
string-ci>? 63
string-copy 64
string-fill! 64
string-length 63; 42
string-ref 63

string-set! 63; 59
string<=? 63
string<? 63
string=? 63
string>=? 63
string>? 63
string? 62; 15
substring 64
symbol->string 59; 16
symbol? 59; 14
syntactic keyword 14; 12, 29, 79
syntax definition 35
syntax-rules 31; 36

#t 52
tail call 17
tan 49
token 79
top level environment 36; 14
transcript-off 78
transcript-on 78
true 15; 22, 23, 52
truncate 48
type 14

unbound 14; 18, 34
unquote 29; 54
unquote-splicing 29; 54
unspecified 10

valid indexes 62; 64
values 71; 20
variable 14; 12, 18, 79
vector 65
vector->list 66
vector-fill! 66
vector-length 65; 42
vector-ref 65
vector-set! 66
vector? 65; 15

whitespace 13
with-input-from-file 75
with-output-to-file 75
write 77; 29
write-char 77

#x 43; 80
zero? 45

Clarifications and corrections

Several inconsistencies in this report have been pointed out since its initial publication on the World-Wide Web. This section addresses the most important of them.

Semantics of call-with-current-continuation

The definition of `call-with-current-continuation` in Section 8.2 is incorrect because it is incompatible with `dynamic-wind`. As shown in Section 4 of [1], however, this incorrect semantics is adequate to define the `shift` and `reset` operators, which can then be used to define the correct semantics of both `dynamic-wind` and `call-with-current-continuation`.

Redefinition of keywords

As stated in Section 3.1, keywords are not reserved. The grammar specified in Section 8.1 is thus somewhat misleading because a program may redefine any or all syntactic keywords. In particular, it is possible to use any identifier as a variable.

Port?

Section 4.2 includes `port?` in the list of predicates defining disjoint types; there is no such procedure. `input-port?` and `output-port?` should be included in this list of predicates. An object may satisfy both `input-port?` and `output-port?`, but cannot satisfy any other pair of predicates in this list.

References

1. Filinski, Andrzej. Representing Monads. In *Proceedings of the 1994 ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, pp. 446–457.